

# OPTIBAR CCT

SLI047400CCT\_PW

LED luminaire OPTIBAR CCT with the possibility of changing the light color (CCT), with a power of 12-42 W, high light efficacy 125 lm/W. Thanks to the ability to change the color temperature (CCT) in the range from 3000K to 6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Narrow beam angle 90° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power	<b>12-42 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5250 lm (360°)</b>	Colour temperature	<b>3000/4000/6000 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>90 °</b>
Degree of protection (IP)	<b>IP20</b>		

## Technical data

---

Code	SLI047400CCT_PW
Power	12-42 W
Nominal current	170 mA
Voltage	230 V
Energy consumption	42 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.95
Useful luminous flux*	5250 lm (360°)
Luminous flux**	1450-5000 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	90 °
RA	90
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	1200x60x90 mm
For use	Inside
Assembly method	on track
Application	Inside
Made in	PRC
Other	Light color change function 3000K/4000K/6000K ,

## Related documents

---



 User manual



 Declaration of Conformity

