# MQ603 Downlight 20W 1650lm 5700K 100° G2

35000 h

15000

3 years



### PRODUCT INFORMATION

Product code 60499 IE-DL-MQ603-20-1650-6000K-1 Product code (long) Product description MQ603 Downlight 20W 1650lm 5999097604992 EAN code Category Downlight

### PHOTOMETRIC DATA

Nominal luminous flux 1650 Lm Rated luminous flux 1650 Lm Nominal beam angle (half-peak value) 100° 100° Rated beam angle (half-peak value) Correlated colour temperature 6000K Colour temperature designation Daylight 80 Ra Colour rendering index (Ra) 7 SDCM Colour consistency

Rated life time

Warranty

Number of switching cycles

Warm-up time to reach 60% of full light 1 s LIFE SPAN Nominal life time 35000 h

### **ELECTRICAL DATA**

20 W Nominal wattage 20,0 W Rated wattage 220-240V Nominal voltage 50/60Hz Operating frequency Nominal current 100 mA Power factor 0.95 Wattage of equivalent filament lamp 150W

240 mm Overal diameter Overall height 53mm Lamp shape Round Weight 0,585 kg

## ADDITIONAL TECHNICAL INFORMATION

IP rating

Starting time 0,5 s Optimum operating ambient temperature 25°C Milky cover Lamp finish Dimming non-dimmable Energy efficiency class 20,0 kWh/100h Energy consumption IP20



