

DG PCB PV SCI 300 FM (952 753)

- Integration of DEHNguard protection modules in the PCBs of electronic / electrical devices
- Easy and flexible use for all circuit configurations
- Coded base part and protection module ensure against installing an incorrect module




Figure without obligation

Dimension drawing DG PCB PV SCI 300 FM

Single-pole base for DEHNguard modules to be mounted on the PCBs of devices, with remote signalling contact for monitoring system (floating changeover contact).

Type	DG PCB PV SCI 300 FM
Part No.	952 753
Associated protection module	DG MOD PV SCI 300 (Part No. 952 053)
Max. continuous operating voltage (d.c.) (module)	300 V
Operating temperature range (T _U)	-40 °C ... +80 °C
For mounting on	directly soldered into PCB
Enclosure material	thermoplastic, red, UL 94 V-0
Degree of protection	IP 20 (protection module plugged in)
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	125 V / 0,1 A
Switching capacity (d.c.)	42 V / 0,5 A; 24 V / 1 A; 12 V / 2 A
Soldering temperature (remote signalling contact)	max. 260 °C / 5 sec.
Weight	18 g
Customs tariff number	85366930
GTIN	4013364150720
PU	72 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.