


Push-in

terminal block 2.5mm², 2-levels, fuse-holder+feed-through, grey color, EFDS series

| | |
|---|---|
| Code | EFDS212GR |
| Type | CPFE.2 + EFDS.2/1S/GR |
| HS code | 85369010 |
| Colour | Grey |
| TECHNICAL FEATURES | |
| Function/Type | 3 levels (fuse-holder + feed-through) |
| Rated cross-section | 2.5 mm ² |
| Connecting capacity | |
| Flexible wire | 0.2-4 mm ² |
| Rigid wire | 0.2-4 mm ² |
| Wire with ferrule - ferrule type | 2.5 mm ² – WP25/19 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 250 V |
| Maximum current (rated cross-section) | 6.3 A (1) |
| Caliber | A3 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 300 V |
| Maximum current (rated cross-section) | 6.3 A (1) |
| Section (min-max) | 24-12 (AWG) |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Rated impulse withstand voltage / pollution degree | 6 kV / 3 |
| Insulation stripping length | 9 mm |
| Width (pitch) | 5.2 mm |
| Length | 110 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 54 / 61.5 / – mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | EFDS.2/PT/GR (cod. EFDS201GR) |
| Blue | – |
| Thickness | 1.5 mm |
| Cross-connection | EFB.2/.../... (cod. EFB02...) |
| Rated current carrying capacity IEC/ATEX | 24 A |
| Coloured partition plate | – |
| Marking | |
| Single marking tag | CNU/8/51 (cod. NU0851S), CNU/10/51 (cod. NU1051S) |
| Single marking tag for pitch insertion | CNU/8/51 (cod. NU0851S), CNU/10/51 (cod. NU1051S) |
| Fuse type | 5x20 mm (1) |
| Conductive element | CO/5 (cod. VL103) |
| Light alarm circuit (12...48 V) | CIL/12–24–48 (cod. CB518) |
| Light alarm circuit (110...230 V) | CIL/115–230 (cod. CB523) |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| DIN rail according to IEC 60715/TH35 | PR/3/.. |
| APPROVALS AND MARKINGS | ma, |



ATTENZIONE:

inserire una piastrina terminale tra due morsetti adiacenti a causa della differenza di spessore tra cartuccia e morsetto.

ATTENTION:

insert an end section between two adjacent terminal blocks, due to the thickness difference between cartridge and terminal block.



* Suitable for 5x20 mm fuses* Accessory with alarm LED, available separately* Accessory with 1 A or 3 A diode, available separately* ATTENTION: insert an end section between two adjacent terminals, due to the difference in thickness between the cartridge and the terminal block.

1 For more details on accessories, refer to the relevant chapters2 (1) Value limited by the certification rating of the fuse

DESCRIZIONE DEL PRODOTTO

CPFE.2+EFDS.2/1P/GR Push-in terminal
block 2.5mm², 2-levels, fuse-holder+feed-through, grey color, EFDS series