


SR D50 3200 FS22 2500 IP HVI GFK V2A (105 315)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination rod $\varnothing 22/16/10$ mm.

Type	SR D50 3200 FS22 2500 IP HVI GFK V2A
Part No.	105 315
Material of air-termination rod	StSt
Length of air-termination rod	2500 mm
Material of supporting tube	GRP / StSt
Length of supporting tube	3200 mm
Transport length	3200 mm
Outside diameter \varnothing	50 mm
Length of insulating clearance	1535 mm
Wall thickness	3 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Max. free length with air-termination rod (wall mounting)	5000 mm
Max. gust wind speed (wall mounting, 1x HVI inside)	188 km/h
Max. gust wind speed (wall mounting, 1x HVI outside)	173 km/h
Max. gust wind speed (wall mounting, 4x HVI outside)	159 km/h
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	12 kg
Customs tariff number	85389099
GTIN	4013364157804
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.