
# **PHILIPS** Lighting



# CorePro GLASS LED candles and lusters

# CorePro LEDCandle ND6.5-60W B35E14827CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

#### **Product data**

| General Information                          |                    |
|--|--------------------|
| Cap-Base                                     | E14                |
| Nominal lifetime                             | 15,000 hour(s)     |
| Switching Cycle                              | 20,000             |
| Lighting Technology                          | LED                |
| Flux measurement reference                   | Sphere             |
|  |                    |
| Light Technical                              |                    |
| Color Code                                   | 827 [CCT of 2700K] |
| Luminous Flux                                | 806 lm             |
| Color Designation                            | Warm White (WW)    |
| Correlated Color Temperature (Nom)           | 2700 K             |
| Luminous Efficacy (rated) (Nom)              | 124.00 lm/W        |
| Color Consistency                            | <6                 |
| Color rendering index (CRI)                  | 80                 |
| LLMF At End Of Nominal Lifetime (Nom)        | 70 %               |
| Photobiological safety according to EN 62471 | RG1                |
|  |                    |

| Operating and Electrical  |             |
|---------------------------|-------------|
| Line Frequency            | 50 to 60 Hz |
| Input Frequency           | 50 to 60 Hz |
| Power Consumption         | 6.5 W       |
| Lamp Current (Nom)        | 50 mA       |
| Wattage Equivalent        | 60 W        |
| Starting Time (Nom)       | 0.5 s       |
| Warm-up time to 60% light | 0.5 s       |
| Power Factor (Fraction)   | 0.55        |
| Voltage (Nom)             | 220-240 V   |
|                           |             |
| Temperature               |             |
| T-Case Maximum (Nom)      | 55 ℃        |
|                           |             |
| Controls and Dimming      |             |
| Dimmable                  | No          |
|                           |             |
|                           |             |




## CorePro GLASS LED candles and lusters


| Mechanical and Housing                             |          |
|--|----------|
| Bulb Finish  | Clear    |
| Bulb Shape   | B35      |
| Net Weight (Piece)                                 | 0.012 kg |
|  |          |
| Approval and Application                           |          |
| Energy Efficiency Class                            | E        |
| Energy Consumption kWh/1000 h                      | 7 kWh    |
| EPREL Registration Number                          | 1825170  |
| CE mark  | Yes      |
| EU RoHS compliant                                  | Yes      |
| EyeComfort   | Yes      |
| Flickering value (PstLM) - Flickering value as per | 1        |
| EN 61000-3-3                                       |          |
| Stroboscopic effect visibility measure (SVM)       | 0.9      |
|  |          |
| Application Conditions                             |          |
| can it be used in closed luminaires                | No       |

| Product Data                    |                             |
|---------------------------------|-----------------------------|
| Order product name              | CorePro LEDCandle ND6.5-60W |
|                                 | B35E14827CLG                |
| Full product name               | CorePro LEDCandle ND6.5-60W |
|                                 | B35E14827CLG                |
| Full product code               | 871951434746500             |
| Order code                      | 929002028092                |
| Material Nr. (12NC)             | 929002028092                |
| Numerator - Quantity Per Pack   | 1                           |
| EAN/UPC - Product/Case          | 8719514347465               |
| Numerator - Packs per outer box | 10                          |
| EAN/UPC - Case                  | 8719514347472               |
|                                 |                             |

#### Dimensional drawing




| Product                                  | D     | C     |
|--|-------|-------|
| CorePro LEDCandle ND6.5-60W B35E14827CLG | 35 mm | 97 mm |
|  |       |       |



Spectral Power Distribution Colour - CorePro LEDCandle ND6.5-60W B35E14827CLG


#### Photometric data



Light Distribution Diagram - CorePro LEDCandle ND6.5-60W B35E14827CLG


### CorePro GLASS LED candles and lusters

#### Photometric data



General uniform lighting - CorePro LEDCandle ND6.5-60W B35E14827CLG

#### Lifetime



B35E14827CLG



 $\odot$  2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2025, March 17 - data subject to change