Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	PHILIPS
-----------------	----------------	---------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier:	9290013910B
-------------------	-------------

_	•			
Type	Λt	liaht	COLL	rco.
IVDE	UI.	HEIIL	3UU	ıce.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G5		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
		General product p	parameters:	
<u> </u>	mption in on- 00 h), rounded st integer	17	Energy efficiency class	Е
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone arrow cone (90º)	2 300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P _{on}), ex-	16,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, (tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	1 163	Spectral power dis-	See image
sions without	Width	19	tribution in the	in last page
separate con- trol gear, light-	Depth	19	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,434
		nates (x and y)	0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value 0 Survival factor		Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

