


VIRGA 2 W0JP10660

LED luminaire VIRGA 2, with a power of 35 W, high light efficacy 115 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 90° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.







www.spectrumled.pl



Technical data

| Code | W0JP10660 |
|------------------------------|----------------|
| Power | 35 W |
| Nominal current | 167 mA |
| Voltage | 230 V |
| Energy consumption | 35 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Manufacturer of power | BRIDGELUX |
| supply | |
| Power factor | 0.93 |
| Useful luminous flux* | 4025 lm (360°) |
| Luminous flux** | 3500 lm (360°) |
| Lamp efficacy | 115 lm/W |
| Colour temperature | 4000 K |
| Colour of light | 940 |
| Beam angle | 90 ° |
| RA | 90 |
| Light source included | Yes |
| Producer of LED diodes | CREE |
| Uniformity of color SDCM max | 3 |
| Working temperature range | -20/+40° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Degree of protection (IP) | IP54/20 |
| Colour | White |
| Dimension (AxBxC) | 230x74 mm |
| Mounting hole | 0210 mm |
| For use | Inside |
| Assembly method | Recessed |
| Application | Inside |
| Made in | PI |
| Made III | |



