

PRODUCT-DETAILS

6127/02-884-500

6127/02-884-500 Control element 4/8gang



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | 6127/02-884-500 |
| Code de produit | 2CKA006117A0242 |
| EAN | 4011395140468 |
| Description courte | 6127/02-884-500 Control element 4/8gang |
| Description longue | For ABB i-bus® KNX 6120/12-101, 6120/13. With labelling field. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. Push switch function: switching / dimming / blind / sending values / scenes etc. Transparent labelling sheet with standard symbols included in delivery. Incl. 10 logic channels (light scene actuator, sequence actuator, logic gates, etc.). |

Installation

| | |
|-------------------------|-----------------|
| Instructions et manuels | 2CKA000073B7442 |
|-------------------------|-----------------|

Technique

| | |
|--|--|
| Fiche produit, informations techniques | DEBJE-th_KNX_Bedienemente_ABB_FR_V1-Spec |
| Number of Buttons | 8 |

| | |
|----------------------------|--|
| Number of Actuation Points | 8 |
| Compatible Bus Systems | KNX (TP) |
| Product Range | KNX |
| Design Range | 63x63 future linear Busch-axcent Busch-axcent pur carat |
| Type de montage | Flush Mounted |
| Finition de surface | Surface protection: Untreated Surface finishing: Matt |
| Matériau | Thermoplastic |
| RAL Number | RAL 9016 - Blanc signalisation |
| Couleur | studio white matt |
| Nombre de batteries | 0 |
| Application Function | Blind / Shutter / Shading Control Electrical Load and Light Control Room Climate Control |

Environnement

| | |
|------------------------------|--|
| Température de l'air ambiant | Operation -5 ... +45 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CKA200000E4448 |
| REACH Declaration | 2CKA309999E9999 |

Dimensions

| | |
|---|-------|
| Produit Largeur Net | 63 mm |
| Produit Hauteur Net | 63 mm |
| Produit Longueur Net | 23 mm |
| Poids net | 36 g |
| Profondeur d'encastrement (t ₂) | 33 mm |

Commande

| | |
|---------------------------|----------------|
| Quantité minimum | 1 pièce |
| Emballage Niveau 1 Unités | carton 1 pièce |
| Emballage Niveau 1 Poids | 0.072 kg |
| Code douanier | 85389099 |
| E-Number (Sweden) | 1750388 |
| Pays d'origine | Germany (DE) |

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité
- CE

2CKA100000E0966

Classifications

| | |
|----------------|--|
| ETIM 8 | EC000672 - Touch sensor for bus system |
| ETIM 9 | EC000672 - Touch sensor for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| DEEE B2C / B2B | Business To Consumer |
| CN8 | 8538 90 99 |
| eClass | V11.0 : 27143138 |

Accessories

| Identifiant | Description | Type | Quantity | Unit Of Measure |
|-----------------|-----------------------------------|-------------|----------|-----------------|
| 2CKA006120A0072 | 6120/13-500 Power bus coupler, FM | 6120/13-500 | 1 | piece |

Catégories

Produits basse tension → Home and Building Automation → KNX → User Operation → Solo → 4/8 fold

