





Push-in terminal block 4mm²,
2-levels interconnected, blue color

| | |
|---|---|
| Series | EFD |
| Code | EFD410BL |
| Type | EFD.4/1+2/BL |
| HS code | 85369010 |
| Colour | Blue |
| TECHNICAL FEATURES | |
| Function/Type | 2 levels with internal connection |
| Rated cross-section | 4 mm ² |
| Connecting capacity | |
| Flexible wire | 0.2-6 mm ² |
| Rigid wire | 0.2-6 mm ² |
| Wire with ferrule - ferrule type | 4 mm ² – WP40/16 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 800 V |
| Maximum current (rated cross-section) | 29 A |
| Caliber | A4 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | 30 A |
| Section (min-max) | 24-10 (AWG) |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | 500 V |
| Maximum current (rated cross-section) | 25 A |
| Operating temperature Min/Max | -40 °C / +110 °C |
| Rated impulse withstand voltage / pollution degree | 6 kV / 3 |
| Insulation stripping length | 10 mm |
| Width (pitch) | 6.2 mm |
| Length | 81.7 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 57.7 / 65.2 / - mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | EFD.4/PT/GR (cod. EFD401GR) |
| Blue | EFD.4/PT/BL (cod. EFD401BL) |
| Thickness | 1.5 mm |
| Cross-connection | |
| Rated current carrying capacity IEC/ATEX | 29 A / 25 A |
| Coloured partition plate | DFE.2P/R (cod. DFE04R) |
| Marking | |
| Adhesive numbering strip | - |
| Snap-on numbering strip | - |
| Single marking tag | CNU/8/51 (cod. NU0851S), CNU/10/51 (cod. NU1051S) |
| Single marking tag for pitch insertion | CNU/8/61 (cod. NU0861S), CNU/10/61 (cod. NU1061S) |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| DIN rail according to IEC 60715/TH35 | PR/3/.. |
| APPROVALS AND MARKINGS |    |



* Reduced wiring time* Wire release push button
1 For more details on accessories, refer to the relevant chapters

DESCRIZIONE DEL PRODOTTO

EFD.4/CI/BL
Push-in terminal block 4mm², 2-levels interconnected, blue color