

## RD 10 STTZN L6000 (800 911)



Figure without obligation

Steel wire according to EN 62561-2 with zinc coating  $\geq 50 \mu\text{m}$  on average (about  $350 \text{ g/m}^2$ ), for use as air-termination system or down conductor in lightning protection systems.

Type	RD 10 STTZN L6000
Part No.	800 911 ✓
Diameter $\varnothing$ conductor	10 mm
Cross-section	$78 \text{ mm}^2$
Material	St/tZn
Standard	based on EN 62561-2
Zinc sheath	$\geq 50 \mu\text{m}$ average (about $350 \text{ g/m}^2$ )
Conductivity	$\geq 6.66 \text{ m} / \text{Ohm mm}^2$
Resistivity	$\leq 0.15 \text{ Ohm mm}^2 / \text{m}$
Short-circuit current (a.c. 50 Hz / d.c.) (1 s; $\leq 300 \text{ }^\circ\text{C}$ )	5.5 kA
Length	6 m
Weight	4,1 kg/Stk
Customs tariff number	72149939
GTIN	4013364273689
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Conductor materials can only be supplied in the original coil weights.

Further conductor materials as specified in the standard series EN 62561-2 are available on request.