



# MASTER - LED HID SON-T

## **MAS LED SON-T IF 6Klm 34W 740 E27**

Philips LED Road lamps are an easy LED solution with a short payback period to replace High Intensity Discharge (HID) and High Pressure Sodium (SON) lamps. TrueForce LED solutions bring the energy efficiency and long lifetime benefits of LED to HID replacement, providing instant savings for a low initial investment. With the right lamp size and light distribution, you can easily retrofit TrueForce LED road lamps into existing SON and SON-T systems, enhancing the lighting quality with LED without changing the luminaire's ballast or reflector.

#### **Warnings and Safety**

· Installation should always be performed by a qualified electrician or installer. Use the installation guide for instructions.

#### **Product data**

| General Information                |                    |
|------------------------------------|--------------------|
| Cap-Base                           | E27 [E27]          |
| Nominal lifetime                   | 70,000 hour(s)     |
| Switching Cycle                    | 50,000             |
| Lighting Technology                | LED                |
| Flux measurement reference         | Sphere             |
|                                    |                    |
| Light Technical                    |                    |
| Color Code                         | 740 [CCT of 4000K] |
| Luminous Flux                      | 6,000 lumen        |
| Color Designation                  | Cool White (CW)    |
| Correlated Color Temperature (Nom) | 4000 K             |
| Luminous Efficacy (rated) (Nom)    | 176 lm/W           |
| Color Consistency                  | <6                 |
| Color rendering index (CRI)        | 70                 |
|                                    |                    |

| LLMF At End Of Nominal Lifetime (Nom) | 70 %            |
|---------------------------------------|-----------------|
|                                       |                 |
| Operating and Electrical              |                 |
| Line Frequency                        | 50 Hz           |
| Input Frequency                       | 50 Hz           |
| Power Consumption                     | 34 W            |
| Lamp Current (Nom)                    | 965 mA          |
| Wattage Equivalent                    | 70 W            |
| Starting Time (Nom)                   | 0.5 s           |
| Warm-up time to 60% light             | 0.5 s           |
| Voltage (Nom)                         | 68-78 V         |
|                                       |                 |
| Temperature                           |                 |
| Ambient temperature range             | -40 °C to 55 °C |
| · · · · · · · · · · · · · · · · · · · |                 |


Datasheet, 2023, May 5 data subject to change

# **MASTER - LED HID SON-T**

| T-Case Maximum (Nom)          | 59 ℃         |
|-------------------------------|--------------|
|                               |              |
| Controls and Dimming          |              |
| Dimmable                      | No           |
|                               |              |
| Mechanical and Housing        |              |
| Bulb Finish                   | Clear        |
| Bulb Material                 | Glass        |
| Bulb Shape                    | T60 [T 60mm] |
|                               |              |
| Approval and Application      |              |
| Energy Consumption kWh/1000 h | 34 kWh       |
| EPREL Registration Number     | 1,077,795    |
| EU RoHS compliant             | Yes          |
|                               |              |


| Product Data                    |                                   |  |
|---------------------------------|-----------------------------------|--|
| Full product code               | 871951444893300                   |  |
| Order product name              | MAS LED SON-T IF 6Klm 34W 740 E27 |  |
| Order code                      | 929003467312                      |  |
| Numerator - Quantity Per Pack   | 1                                 |  |
| Numerator - Packs per outer box | 6                                 |  |
| Material number (12NC)          | 929003467312                      |  |
| Net weight                      | 0.250 kg                          |  |
| Full product name               | MAS LED SON-T IF 6Klm 34W 740 E27 |  |
| EAN/UPC - Case                  | 8719514448940                     |  |
|                                 |                                   |  |


# Dimensional drawing



| Product                           | D     | С      |
|-----------------------------------|-------|--------|
| MAS LED SON-T IF 6Klm 34W 740 E27 | 61 mm | 200 mm |

## Photometric data






Light Distribution Diagram


## **MASTER - LED HID SON-T**


#### Photometric data



Spectral Power Distribution Colour

## Lifetime





Life Expectancy Diagram - MAS LED SON-T IF 6Klm 34W 740 E27

Lumen Maintenance Diagram - MAS LED SON-T IF 6Klm 34W 740 E27



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.