

PRODUCT DATASHEET VALUE CLAS A 75 10 W/6500 K E27

LED CLASSIC A V | LED lamps, classic bulb shape



Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Product features

- Professional LED lamps for line voltage
- Not dimmable
- Lifetime up to 15,000 h
- Good quality of light; color rendering index R_a : \geq 80; constant chromaticity




TECHNICAL DATA

Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	70 mA
Type of current	AC
Inrush current	10 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	133
Max. lamp number on MCB B16 A	213
Total harmonic distortion	73 %
Power factor λ	0.65

Photometrical data

Luminous flux	1055 lm
Luminous efficacy	105 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.9



LISO spectral power distribution 6500K CRI80 v2

Light technical data

Beam angle	150 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	109.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	26.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	88 °C

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

Capabilities

Dimmable	No
Certificates & Standards	
Energy efficiency class	F

Energy consumption	10.00 kWh/1000h	
Type of protection	IP20	
Standards	ROHS 2.0 / REACH / CE / CB / ERP	
Photobiological safety group acc. to EN62778	RG1	
Country-specific categorizations		
Order reference	VALUECLA75 10W/	
LOGISTICAL DATA		
Temperature range at storage	-20+80 °C	
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	
Non-directional or directional	NDLS	
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	E27	
Connected light source (CLS)	No	
Color-tuneable light source	No	
Envelope	No	
High luminance light source	No	
Anti-glare shield	No	
Correlated colour temperature type	SINGLE_VALUE	
Standby power	0 W	
Networked standby power for CLS	0 W	
Claim of equivalent power	Yes	
Length	109.00 mm	
Height	60.00 mm	
Width	60.00 mm	
Chromaticity coordinate x	0.312	
Chromaticity coordinate y	0.328	
R9 Colour rendering index	>0	
Beam angle correspondence	SPHERE_360	
Survival factor	0.90	
Displacement factor	0.50	
LED light source replaces a fluorescent light source	No	
EPREL ID	1381371,1857047,1855175	
Model number	AC44920,AC55988,AC56440,AC55988	

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Photometric and lighting design files	Document name	
1	Spectral power distribution	LISO spectral power distribution 6500K CRI80 v2	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854073724	Folding box 1	60 mm x 60 mm x 112 mm	40.00 g	0.40 dm ³
4099854073731	Shipping box 10	315 mm x 132 mm x 126 mm	496.00 g	5.24 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.