## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 9290035789

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	2G11				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Froduct parameters					
	Value	Parameter	Value		
General product parameters:					
00 h), rounded	8	Energy efficiency class	E		
ers to the flux in , in a wide cone	1 000 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	4 000		
ver (P <sub>on</sub> ), ex-	8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
expressed in W	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Height	224	Spectral power dis-	See image		
Width Depth	38 17	tribution in the range 250 nm to 800 nm, at full-load	in last page		
	andby power expressed in W the second dec- Height Width	ValueGeneral product pnption in on- 00 h), rounded st integers flux (\$\phiuse\$), in- ers to the flux in , in a wide cone irrow cone (90°)ver (Pon), ex- expressed in W the second dec-Height Width224 Width	ValueParameterGeneral product parameters:nption in on- 00 h), rounded st integer8Energy efficiency classs flux (фuse), in- ers to the flux in , in a wide cone prrow cone (90°)1 000 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be setver (Pon), ex-8,0Standby power (Psb), expressed in W the second dec-andby power expressed in W the second decColour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be setHeight224Spectral power dis- tribution in the range 250 nm to 800		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,382		
		nates (x and y)	0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

