## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 9290030870

## Type of light source:

Anti-glare shield:	No	Dimmable:	No
High luminance light source:	No		
Colour-tuneable light source:	No	Envelope:	-
Mains or non-mains:	NMLS	Connected light source (CLS):	No
(or other electric interface)			
Light source cap-type	GU4		
Lighting technology used:	LED	Non-directional or directional:	DLS

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 00 h), rounded st integer	4	Energy efficiency class	G		
indicating if it rains if it rains in a sphere (30	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	200 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode p expressed in W	oower (P <sub>on</sub> ),	3,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	40	Spectral power	See image		
dimensions	Width	35	distribution in the	in last page		
without	Depth	35		Page 1/3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	20				
		Chromaticity coordinates (x and y)	0,458 0,410				
Parameters for directional light sources:							
Peak luminous intensity (cd)	1 000	Beam angle in degrees, or the range of beam angles that can be set	24				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	0	Survival factor	0,90				
the lumen maintenance factor	0,96						

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

