



# MASTER TL5 High Efficiency

# **MASTER TL5 HE 35W/840 SLV/40**

This TL5 lamp (tube diameter 16 mm) has a high luminous efficacy, resulting in low energy consumption. The High Efficiency TL5 lamp offers excellent lumen maintenance and good color rendering. Application areas are offices, industry, public and governmental buildings, schools, hospitals and indoor sports lighting.

## **Warnings and Safety**

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information					
Cap-Base	G5 [G5]				
Features	na [Not Applicable]				
Flux measurement reference	Sphere				
Light Technical					
Color Code	840 [CCT of 4000K]				
Luminous Flux	3,315 lumen				
Color Designation	Cool White (CW)				
Chromaticity Coordinate X (Nom)	0.38				
Chromaticity Coordinate Y (Nom)	0.38				
Correlated Color Temperature (Nom)	4000 K				
Luminous Efficacy (rated) (Nom)	94 lm/W				
Color rendering index (CRI)	80				

Operating and Electrical			
Power Consumption	34.9 W		
Lamp Current (Nom)	0.175 A		
Controls and Dimming			
Dimmable	Yes		
Mechanical and Housing			
Bulb Shape	T5 [16 mm (T5)]		
Approval and Application			
Mercury (Hg) Content (Nom)	1.2 mg		
Energy Consumption kWh/1000 h	35 kWh		
EPREL Registration Number	423,543		

Datasheet, 2023, May 16 data subject to change

# **MASTER TL5 High Efficiency**


Product Data			
Full product code	871150063952355		
Order product name	MASTER TL5 HE 35W/840 SLV/40		
Order code	927927084055		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	40		

Material number (12NC)	927927084055		
Full product name	MASTER TL5 HE 35W/840 SLV/40		
EAN/UPC - Case	8711500867681		

## Dimensional drawing


Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 35W/840	17 mm	1,449.0 mm	1,456.1 mm	1,453.7 mm	1,463.2 mm
SLV/40					


#### Photometric data



Spectral Power Distribution Colour - MASTER TL5 HE 35W/840 SLV/40

## Lifetime





Life Expectancy Diagram - MASTER TL5 HE 35W/840 SLV/40

Life Expectancy Diagram - MASTER TL5 HE 35W/840 SLV/40

# **MASTER TL5 High Efficiency**

## Lifetime



Lumen Maintenance Diagram - MASTER TL5 HE 35W/840 SLV/40



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.