

QBLOK1203

Single-pole terminal block 12x10mm2, grey

| • | | |
|---|--|---|
| Series | QBLOK | |
| Code | QBLOK1203 | |
| Туре | QBLOK.12/GR | |
| HS code | 85369010 | |
| Colour | Grey | _ |
| TECHNICAL FEATURES | | |
| Function/Type | Distribution terminal board | |
| Number and rated cross connection | | |
| <u>A</u> | | |
| В | | |
| <u>C</u> | | |
| D | | |
| Input A | | |
| Rated cross-section | 12 x 10 mm² | |
| Connecting capacity (flexible) | 1.5–10 mm ² | |
| Connecting capacity (rigid) | 1.5–16 mm ² | |
| Connecting capacity (with ferrule) | 10 mm ² - WP 100/21 | |
| Supply bar dimension | | |
| Output B | | |
| Rated cross-section | - | |
| Connecting capacity (flexible) | - | |
| Connecting capacity (rigid) | - | - |
| Connecting capacity (with ferrule) | - | |
| Output C | | - |
| Rated cross-section | - | |
| Connecting capacity (flexible) | _ | |
| Connecting capacity (rigid) | _ | |
| Connecting capacity (with ferrule) | _ | |
| Output D | | |
| Rated cross-section | - | |
| Connecting capacity (flexible) | _ | |
| Connecting capacity (rigid) | _ | |
| Connecting capacity (with ferrule) | _ | |
| Electrical characteristics according to IEC EN standard | | |
| Maximum voltage AC/DC | 500 V | |
| Maximum current (rated cross-section) | 63 A | |
| · · · · | | |
| Caliber | 85 | |
| Caliber Electrical characteristics according to UL Standard | B5 | |
| Electrical characteristics according to UL Standard | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) | - - - | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) | - - - - | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) | - - - - | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) | - - - - | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (lpk) Rated impulse withstand voltage / pollution degree | - - - - - | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length | - - - - - - 6 mm | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) | - - - - - 6 mm 2 / 2.5 Nm | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material | - - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) | - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 16 mm | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (lcw) (value effective for 1s) Peak current (lpk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length | - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 16 mm 85 mm | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 | - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 16 mm 85 mm 33 / 41 mm | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting | - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 16 mm 85 mm | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (non. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES | - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 16 mm 85 mm 33 / 41 mm | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking | - - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 16 mm 85 mm 33 / 41 mm - | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag | - - - - - - 6 mm 2 / 2.5 Nm Polyamide UL94V-0 16 mm 85 mm 33 / 41 mm - | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag End bracket | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widh (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag End bracket TH35 screw type | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (Icw) (value effective for 1s) Peak current (Ipk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widh (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag End bracket TH35 screw type TH35 snap-fit type | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (lcw) (value effective for 1s) Peak current (lpk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (lcw) (value effective for 1s) Peak current (lpk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 snap-fit type TH35 and G32 snap-fit type Mounting rail | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (lcw) (value effective for 1s) Peak current (lpk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (non. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type TH35 and G32 snap-fit type Mounting rail DIN rail according to IEC 60715/TH35 | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (lcw) (value effective for 1s) Peak current (lpk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (nom. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 snap-fit type TH35 and G32 snap-fit type Mounting rail | | |
| Electrical characteristics according to UL Standard Maximum voltage AC/DC Maximum current (rated cross-section) Section (min-max) Tightening torque value (UL) Short term current allowed (lcw) (value effective for 1s) Peak current (lpk) Rated impulse withstand voltage / pollution degree Insulation stripping length Tightening torque value (non. / max.) Plastic material Widht (pitch) Length Height mounted on TH35-7.5/TH35-15 Height for panel mounting ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type TH35 and G32 snap-fit type Mounting rail DIN rail according to IEC 60715/TH35 | | |





QBLOK1203



* IP20 protegtion degree* Marking possible with a CNU/8 or CNU/10 tag* Available in grey, green and blue colors* Selfextinguishing plastic material 1 For more details, refer to the data sheet

DESCRIZIONE DEL PRODOTTO

QBLOK.12/GR Single-pole terminal block 12x10mm2, grey