

Product Data Sheet

GW20517



SYSTEM WHITE - Domestic range



Wide range of control devices, sockets for power supply (conforming to national and international standards) signal pick-up, climate control, comfort management, technical alarm signalling and emergency lighting management. The System modular devices are available in two colours, shiny white and satin black. Thanks to the mounting supports for rectangular and square boxes, endless combinations can be created with the Top System and Virna range of plates.

| | | | |
|---|--------------------------------|--|------------------------------|
| Category | Push-button | Button key | Neutral |
| Symbol | Double circle | Colour | Glossy white |
| Description | 2P NO - 10A | Voltage | 250 V ac |
| Standard | EN 60669-1 | Resistance at test voltage | 2000 V at 50 Hz for 1 minute |
| Insulation resistance | > 5 MOhm | Wiring terminals | With screw |
| Prolonged operation switch (no.of position changes) | 40.000 at In 250 V ac cosφ=0,6 | Thermo-pressure with ball | 125 °C |
| Glow Wire Test | 850 °C | Terminal grip on cable traction | > 50 N |
| Terminal tightening capacity stranded cables (mm ²) | min. 0,75 - max. 2x4 | Terminal tightening capacity solid cables (mm ²) | min. 0,5 - max. 2x2,5 |
| Electrocod | 0130 | | |

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

