



CorePro LEDcapsule LV



CorePro LEDcapsuleLV 1.8-20W GY6.35 830

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information	
Cap-Base	GY6.35
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	215 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	119.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	1.8 W
Lamp Current (Nom)	260 mA
Wattage Equivalent	20 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.6
14 II	
Voltage (Nom)	ac electronic 12 V
Voltage (Nom)	ac electronic 12 V
Temperature	ac electronic 12 V
	ac electronic 12 V
Temperature	
Temperature	
Temperature T-Case Maximum (Nom)	
Temperature T-Case Maximum (Nom) Controls and Dimming	80 °C
Temperature T-Case Maximum (Nom) Controls and Dimming	80 °C


Datasheet, 2025, March 17 data subject to change

CorePro LEDcapsule LV

Net Weight (Piece)	0.008 kg
Approval and Application	
Energy Efficiency Class	E
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	2 kWh
EPREL Registration Number	374878
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per	0.4
EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	1
Application Conditions	
can it be used in closed luminaires	No


Product Data	
Order product name	CorePro LEDcapsuleLV 1.8-20W
	GY6.35 830
Full product name	CorePro LEDcapsuleLV 1.8-20W
	GY6.35 830
Full product code	871869976783900
Order code	929002389802
Material Nr. (12NC)	929002389802
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699767839
Numerator - Packs per outer box	12
EAN/UPC - Case	8718699767846

Dimensional drawing




Product	D	С
CorePro LEDcapsuleLV 1.8-20W GY6.35 830	13 mm	35 mm

Photometric data








Spectral Power Distribution Colour - CorePro LEDcapsuleLV 1.8-20W GY6.35 830


CorePro LEDcapsule LV


Photometric data



Light Distribution Diagram - CorePro LEDcapsuleLV 1.8-20W GY6.35 830

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro LEDcapsuleLV 1.8-20W GY6.35 830



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.