



Screw terminal block 10mm²
portafusibile, 1-level, with lamp predisposition, beige color

Series	FPC – FPL
Code	FP200
Type	FPL.10/L
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Fuse-holder 6.3×32 with alarm (1)
Rated cross-section	10 mm ²
Connecting capacity	
Flexible wire	1.5-16 mm ²
Rigid wire	1.5-16 mm ²
Wire with ferrule - ferrule type	10 mm ² – WP100/21
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	800 V
Maximum current (rated cross-section)	10 A (20 A con SFC/CO)
Caliber	B6
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	300 V
Maximum current (rated cross-section)	15 A
Section (min-max)	20-6 (AWG)
Tightening torque value (UL)	7 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Rated impulse withstand voltage / pollution degree	6 kV / 3 (2)
Insulation stripping length	17 mm
Tightening torque value (nom. / max.)	1.2 / 1.9 Nm
Width (pitch)	12 mm
Length	63 mm
Height mounted on TH35-7.5/TH35-15/G32	71 / 79 / 75 mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Blue	-
Beige	-
Thickness	-
Cross-connection	
Model A)	-
Model B)	-
Rated current carrying capacity IEC/ATEX	-
Cross-connection identification strip	-
Coloured partition plate	DFU/6/R (cod. DU06R)
Cross-connection barrier	-
Test plug socket	-
Test plug	-
Connection knob	MSM (cod. FC103) (3)
Marking	
Snap-on numbering strip	CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S)
Single marking tag	-
Fuse type	6.3×32 mm (1)
Conductive element	SFC/CO (cod. FC102)
Light alarm circuit (12...48 V)	cod. FL201 (12 – 48V)
Light alarm circuit (110...230 V)	FL202 (70 – 380V)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	
	



* Suitable for 6.3x32 mm fuses* Accessory with alarm LED, available separately* End section plate is not required
1 For more details on accessories, refer to the relevant chapters2 (1) Value referred to the insulation characteristics of the terminal blocks3 (2) An optional light alarm is available

DESCRIZIONE DEL PRODOTTO

FPL.10/L Screw
terminal block 10mm² portafusibile, 1-level, with lamp predisposition,
beige.color