



MASTER Value LEDtube T8

MAS LEDtube VLE 1200mm UO 15.5W 865 T8

A high-performance LED solution, the professional MASTER Value LED tube is ideal for replacing T8 fluorescent lamps using EM ballast or installing directly on the mains. This product provides an optimal combination of value and performance — for use in all general lighting, office, industry, retail, and hospitality applications. The unique design of this LED T8 tube light offers wide compatibility, safety and fast installation, as well as instant energy savings.

Product data

General Information					
Cap-Base	G13 [Medium Bi-Pin Fluorescent]				
Nominal lifetime	60,000 hour(s)				
Switching Cycle	200,000				
Lighting Technology	LED				
Flux measurement reference	Sphere				
Light Technical					
Color Code	865 [CCT of 6500K]				
Beam Angle (Nom)	190 degree(s)				
Luminous Flux	2,500 lumen				
Color Designation	Cool Daylight				
Correlated Color Temperature (Nom)	6500 K				
Luminous Efficacy (rated) (Nom)	161 lm/W				
Color Consistency	<6				
Color rendering index (CRI)	80				
LLMF At End Of Nominal Lifetime (Nom) 70 %					

Operating and Electrical			
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		
Power Consumption	15.5 W		
Starting Time (Nom)	0.5 s		
Warm-up time to 60% light	0.5 s		
Power Factor (Fraction)	0.9		
Voltage (Nom)	220-240 V		
Temperature			
Ambient temperature range	-20 °C to 45 °C		
T-Case Maximum (Nom)	60 ℃		
Controls and Dimming			
Dimmable	No		
Mechanical and Housing			
Bulb Finish	Frosted		
Bulb Material	Glass		


Datasheet, 2023, May 22 data subject to change

MASTER Value LEDtube T8

Product Length	1,200 mm				
Bulb Shape	Tube, double-ended				
Approval and Application					
Energy Saving Product	Yes				
Approval Marks	RoHS compliance TUV CE marking KEMA Keu				
	certificate				
Energy Consumption kWh/1000 h	16 kWh				
EPREL Registration Number	1,095,873				
CE mark	Yes				
EU RoHS compliant	Yes				


Product Data					
Full product code	871951431684300				
Order product name	MAS LEDtube VLE 1200mm UO 15.5W 865 T				
Order code	929002997802				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	10				
Material number (12NC)	929002997802				
Full product name	MAS LEDtube VLE 1200mm UO 15.5W 865 T8				
EAN/UPC - Case	8719514316850				

Dimensional drawing




Product	D1	D2	A1	A2	А3
MAS LEDtube VLE 1200mm UO	25.8 mm	28 mm	1,198.2 mm	1,205.3 mm	1,212.4 mm
15.5W 865 T8					

Photometric data




Spectral Power Distribution Colour - MAS LED tube VLE 1200mm UO 15.5W $865\,T8$




MASTER Value LEDtube T8


Photometric data




Light Distribution Diagram - MAS LEDtube VLE 1200mm UO 15.5W 865 T8

Lifetime






Life Expectancy Diagram - MAS LEDtube VLE 1200mm UO 15.5W $865\,\mathrm{T8}$



Life Expectancy Diagram - MAS LEDtube VLE 1200mm UO 15.5W $865\,\mathrm{T8}$




Lumen Maintenance Diagram - MAS LEDtube VLE 1200mm UO 15.5W 865 T8

Life Expectancy Diagram - MAS LEDtube VLE 1200mm UO 15.5W 865 T8

MASTER Value LEDtube T8

Lifetime



Lumen Maintenance Diagram - MAS LEDtube VLE 1200mm UO 15.5W 865 T8



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.