

# PRODUCT DATASHEET CLA A FR 100 13 W/4000 K E27

LED Antibacterial Classic | Consumer Antibacterial Led Lamp With Classic Bulb



## Areas of application

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

#### **Product benefits**

- Very low energy consumption
- Can be easily fitted instead of ordinary light bulbs
- Decompose and neutralize odors
- Harmless to humans and animals
- Fights airborne germs: Escherichi coli, H1N1 (Flu)

#### **Product features**

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering (R<sub>a</sub>  $\ge$  80) and color stability throughout the life of the lamp




## **TECHNICAL DATA**

## **Electrical data**

Nominal wattage	13 W	
Construction wattage	13.00 W	
Nominal voltage	220240 V	
Claimed equiv. conventional lamp power	100 W	
Nominal current	108 mA	
Type of current	AC	
Operating frequency	5060 Hz	
Mains frequency	5060 Hz	
Total harmonic distortion	150 %	
Power factor $\lambda$	> 0.50	

#### Photometrical data

Luminous flux	1521 lm
Nominal useful luminous flux 90°	1521 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 К
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.9




# Light technical data

Beam angle

200 °

#### Starting time

# **Dimensions & Weight**



Overall length	118.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	50.00 g

## Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

## Additional product data

Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

# Capabilities

Dimmable No	
-------------	--

# **Certificates & Standards**

Energy efficiency class	F <sup>1)</sup>
Energy consumption	13.00 kWh/1000h
Type of protection	IP20
Photobiological safety group acc. to EN62778	RGO

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

## **Country-specific categorizations**

Order reference	LCCLA100 13W/84
-----------------	-----------------

## Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type SINGLE_VALUE	
Standby power	0.00 W
Networked standby power for CLS	0.00 W
Claim of equivalent power	Yes
Length	118.00 mm
Height	60.00 mm
Width	60.00 mm
Chromaticity coordinate x	0,3818
Chromaticity coordinate y	0,3797
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0.5
Displacement factor	≥0.7
LED light source replaces a fluorescent light source	No
EPREL ID	1403212,523300,734824
Model number	AC31142,AC36886,AC24696

# DOWNLOAD DATA

	Documents and certificates
PDF	Declarations Of Conformity CE
	Photometric and lighting design files
1	IES file (IES)
	LDC typ polar
1	Spectral power distribution

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075560895	Folding box 1	62 mm x 62 mm x 122 mm	55.00 g	0.47 dm <sup>3</sup>
4058075560901	Shipping box 10	319 mm x 133 mm x 138 mm	500.00 g	5.85 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.