




## 10/100Mbps slim fast ethernet switch 8-RJ45, unmanaged

<b>Series</b>	SWE-T
<b>Code</b>	XSWET8PU
<b>Type</b>	SWE-T-8PU
<b>HS code</b>	85176200
<b>Version</b>	8 – RJ45 unmanaged
<b>Interface</b>	
<b>Number and type of interface</b>	8 RJ45 ports
<b>Connection method</b>	Auto negotiation, Full/Half duplex mode, auto MDI/MDI-X connection
<b>Transmission speed</b>	10/100 Mbps
<b>MAC table size</b>	2K
<b>Status indication</b>	Power, Link/Speed, Link /Activity
<b>GENERAL TECHNICAL DATA</b>	
<b>Power supply voltage</b>	12...36 Vdc / 10...24 Vac
<b>Current consumption</b>	170 mA
<b>Operating temperature range</b>	-10...+60°C
<b>Ambient temperature range</b>	-10...+60°C
<b>Standards</b>	IEEE802.3, 802.3u, 802.3x
<b>Safety Standard</b>	EN 62368-1
<b>EMC Standard</b>	EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-6-2
<b>Overvoltage category /pollution degree</b>	I / 2
<b>Protection degree</b>	IP 30
<b>Connection type</b>	1.5 mm <sup>2</sup> (screw)
<b>Housing material</b>	metallic
<b>Dimensions (LxHxD)</b>	24x145x75 mm
<b>Approximate weight</b>	465 g
<b>Mounting information</b>	on a rail, side by side
<b>APPROVALS AND MARKINGS</b>	FC, CE,
<b>ACCESSORIES</b>	
<b>Mounting rail (IEC60715/TH35-7.5)</b>	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
<b>Mounting rail (IEC60715/TH35-15)</b>	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB



\* 5 and 8 port fast ethernet switch unmanaged\* Designed to meet Level 3 (Heavy) industrial environments\* Panel and DIN rail mountable

## DESCRIZIONE DEL PRODOTTO

SWET-8PU  
10/100Mbps slim fast ethernet switch 8-RJ45, unmanaged