

# PRODUCT DATASHEET LUMILUX T5 HE 21W-865 20X1 RU OSRAM

LUMILUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency, with G5 base



## Areas of application

- Public buildings
- Offices
- Shops
- Supermarkets and department stores
- Industry
- Outdoor applications only in suitable luminaires

### Product benefits

- Up to 20 % more economical than LUMILUX® T8

## **Product features**

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



## TECHNICAL DATA

## Electrical data

Nominal wattage	21 W
Construction wattage	20.70 W
Nominal voltage	126 V
Nominal current	0.17 A

## Photometrical data

Luminous flux	1925 lm
Luminous efficacy	91 lm/W
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89

## **Dimensions & Weight**

Overall length	863.20 mm
Diameter	16.00 mm
Product weight	70.92 g

## Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.97
Rated lamp survival factor at 20,000 h	0.85

# Additional product data

Base (standard designation)	G5
Mercury content	1.5 mg

#### Capabilities

Dimmable Yes	
--------------	--

## Certificates & Standards

Energy efficiency class	F
Energy consumption	21.00 kWh/1000h

## Country-specific categorizations

Order reference	HE 21W/865

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G5
Correlated colour temperature type	SINGLE_VALUE
Length	863.20 mm
Height	16.00 mm
Width	16.00 mm
EPREL ID	546268
Model number	AC34032

## Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854128158	Sleeve 1	18 mm x 18 mm x 863 mm	86.00 g	0.28 dm <sup>3</sup>
4099854128165	Shipping box 20	891 mm x 104 mm x 88 mm	1901.00 g	8.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.