DL120 Downlight Round 6W 420lm 4000K 120° G2



PRODUCT INFORMATION

Product code 60359

Product code (long) IE-DL-DLR130-6-420-4000K-12
Product description DL120 Downlight Round 6W

EAN code 5999097603599
Category Downlight

PHOTOMETRIC DATA

Nominal luminous flux 420 lm Rated luminous flux 420 lm Rated useful luminous flux 70 110° Nominal beam angle (half-peak value) Rated beam angle (half-peak value) 110° Correlated colour temperature 4000K Colour temperature designation neutral white 80 Ra Colour rendering index (Ra) 6 SDCM Colour consistency Warm-up time to reach 60% of full light 2 s Suitable for accent lighting

ELECTRICAL DATA

Nominal wattage 6 W
Rated wattage 6.0 W
Nominal voltage 220-240V
Operating frequency 50/60Hz
Nominal current 260 mA
Power factor 0.5

Overal diameter 120 mm

Overall height 21 mm

Lamp shape Round

Weight 0,175 kg

Mounting D110 mm cutout

LIFE SPAN

Nominal life time30 000 hrsRated life time30 000 hrsNumber of switching cycles15000Lumen main.fact.at end of nom.life time70%Warranty3 years

ADDITIONAL TECHNICAL INFORMATION

IP rating

Starting time 3,0 s

Optimum operating ambient temperature -20°C - +40°C

Lamp finish Milky cover

Dimming non-dimmable

Energy efficiency class A+

Energy consumption 6 kWh/100h

Electrical protection class Class II

IP20



