



CoreLine Downlight

DN140B LED10S/840 PSU WR PI6

- 840 neutral white - Power supply unit (ON/OFF) - White reflector without louver - Push-in connector 6-pole - IP20 | Finger-protected

CoreLine Downlight delivers on the CoreLine promise of innovative, easy to use and high-quality recessed downlights. The CoreLine Downlight range is suitable for one-to-one conventional luminaire replacements, with an attractive TCO that helps customers to make the switch to LED. These recessed downlights create uniform light distribution for use in general lighting applications. They also deliver instant energy savings and have a much longer lifetime, creating a real value-for-money and environmentally-friendly solution. CoreLine DN140B recessed downlights are easy to install thanks to their standard cut-out size and push-in connectors. An InterAct Ready option with integrated wireless communications is available in this family, which can be used with InterAct gateways, sensors and software.

Product data

General Information		Service tag	
Light source replaceable	No	Service tag	Yes
Number of gear units	1 unit	Lighting Technology	LED
Driver included	Yes	Value ladder	Performance
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.	Light Technical	
		Luminous Flux	1,100 lumen
		Saturated Red (R9)	<50
		Correlated Color Temperature (Nom)	4000 K
		Luminous Efficacy (rated) (Nom)	116 lm/W
		Color rendering index (CRI)	≥80
		Beam angle of light source	120 degree(s)
		Light source color	840 neutral white

CoreLine Downlight

Optic type	-
Luminaire light beam spread	90°
Unified glare rating CEN	25

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Power Consumption	9.5 W
End CLO power consumption	- W
Inrush current	2.2 A
Inrush time	0.045 ms
Power Factor (Fraction)	0.95
Connection	Push-in connector 6-pole
Cable	-
Number of products on MCB of 16 A type B	48

Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	White
Optical cover/lens finish	Frosted
Reflector Finish	White reflector
Overall length	0 mm
Overall width	0 mm
Overall height	100 mm
Overall diameter	162 mm
Dimensions (Height x Width x Depth)	100 x 0 x 0 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 850 °C, duration 5 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Warranty period	5 years
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.381,0.379) SDCM≤5
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	1 %
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L70

Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

Product Data

Full product code	871016332581100
Order product name	DN140B LED10S/840 PSU WR P16
EAN/UPC - Product	8710163325811
Order code	911401631105
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	911401631105
Full product name	DN140B LED10S/840 PSU WR P16
EAN/UPC - Case	8710163334738



CoreLine Downlight

Dimensional drawing

