





MASTER UltraEfficient LED candles and lusters

MAS LEDCandleND2.3-40W E14 827 B35CL GUE

This is the most efficient LED candle from Philips brand. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only the high SPEC product, but also keep the light quality of Philips brand

Product data

General Information	
Cap-Base	E14 [E14]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
EU RoHS compliant	Yes
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux	485 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	210 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM)	1

Stroboscopic effect value (SVM)	0.4
Photobiological safety according to EN	RG1
62471	
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	2.3 W
Lamp Current (Nom)	25 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (Nom)	220-240 V
Voltage (Nom)	220 V
Temperature	
Ambient temperature range	-20 to +45 °C

Datasheet, 2023, October 10 data subject to change

MASTER UltraEfficient LED candles and lusters


T-Case Maximum (Nom)	70 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	B35 [B 35mm]
Approval and Application	
Energy Efficiency Class	А
Energy Consumption kWh/1000 h	3 kWh
EPREL Registration Number	1443705
Photobiological risk	Photobiological risk group 1 @ 200mm to
	EN62471


EyeComfort	Yes
Product Data	
Full product code	872016918893800
Order product name	MAS LEDCandleND2.3-40W E14 827 B35CL
	GUE
Order code	929003625902
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929003625902
Full product name	MAS LEDCandleND2.3-40W E14 827 B35CL
	GUE
EAN/UPC - Case	8720169188945
EAN/UPC - Product/Case	8720169188938


Dimensional drawing

Product	D	С
MAS LEDCandleND2.3-40W E14 827 B35CL GUE	35 mm	111 mm

Photometric data








Light Distribution Diagram - MAS LEDCandleND2.3-40W E14 827 B35CL GUE

MASTER UltraEfficient LED candles and lusters


Photometric data




Closus Reconstrol 45 Philips Lighting BV. Page 1

General uniform lighting - MAS LEDCandleND2.3-40W E14 827 B35CL GUE

Lifetime





Life Expectancy Diagram - MAS LEDCandleND2.3-40W E14 827 B35CL GUE

Lumen Maintenance Diagram - MAS LEDCandleND2.3-40W E14 827 B35CL GUE



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.