



CorePro Plastic LEDcandles & lusters



CorePro candle ND 7-60W E14 840 B38 FR

The CorePro LEDcandles and lusters are designed for retrofit replacement of incandescent lamps and are particularly attractive for chandeliers. They are compatible with fixtures with an E14 holder for candles and E14 or E27 holders for lusters and are available in multiple color temperatures. LED lamps deliver huge energy savings of up to 80% energy-saving compared with halogen lamps and provide excellent quality of light. By offering a lifetime of 15,000 hours it lowers maintenance costs. The CorePro LED candles and lusters are perfect for your basic lighting needs.

Product data

General Information		
Cap-Base	E14	
Nominal lifetime	15,000 hour(s)	
Switching Cycle	50,000	
Lighting Technology	LED	
Light Technical		
Color Code	840 [CCT of 4000K]	
Luminous Flux	806 lm	
Color Designation	Cool White (CW)	
Correlated Color Temperature (Nom)	4000 K	
Luminous Efficacy (rated) (Nom)	115.00 lm/W	
Color Consistency	<6	
Color rendering index (CRI)	80	
LLMF At End Of Nominal Lifetime (Nom)	70 %	
Photobiological safety according to EN 62471	RG1	

Operating and Electrical		
Line Frequency	50 to 60 Hz	
Input Frequency	50 to 60 Hz	
Power Consumption	7 W	
Lamp Current (Nom)	59 mA	
Wattage Equivalent	60 W	
Starting Time (Nom)	0.5 s	
Warm-up time to 60% light	0.5 s	
Power Factor (Fraction)	0.51	
Voltage (Nom)	220-240 V	
Temperature		
T-Case Maximum (Nom)	87 °C	
Controls and Dimming		
Dimmable	No	


Datasheet, 2025, March 17 data subject to change

CorePro Plastic LEDcandles & lusters

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	B38
Net Weight (Piece)	0.053 kg
Approval and Application	
Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	453211
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Application Conditions	
can it be used in closed luminaires	No


Product Data	
Order product name	CorePro candle ND 7-60W E14 840
	B38 FR
Full product name	CorePro candle ND 7-60W E14 840
	B38 FR
Full product code	871951431298200
Order code	929002972702
Material Nr. (12NC)	929002972702
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514312982
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514312999

Dimensional drawing




Product	D	С
CorePro candle ND 7-60W E14 840 B38 FR	38 mm	114 mm

Photometric data




Light Distribution Diagram - CorePro candle ND 7-60W E14 840 B38 FR



Spectral Power Distribution Colour - CorePro candle ND 7-60W E14 840 B38

CorePro Plastic LEDcandles & lusters


Photometric data




CataLux Reconstrict 45 Philips Lighting B.V. Page: 1

General uniform lighting - CorePro candle ND 7-60W E14 840 B38 FR

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro candle ND 7-60W E14 840 B38 FR



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.