



Sping-clamp  
terminal block 10mm<sup>2</sup>, 1-level, grey color



<b>Series</b>	HMM
<b>Code</b>	HM330GR
<b>Type</b>	HMM.10/GR
<b>HS code</b>	85369010
<b>Colour</b>	grey
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Feed-through
<b>Rated cross-section</b>	10 mm <sup>2</sup>
<b>Connecting capacity</b>	
<b>Flexible wire</b>	1.5-16 mm <sup>2</sup>
<b>Rigid wire</b>	1.5-16 mm <sup>2</sup>
<b>Wire with ferrule - ferrule type</b>	10 mm <sup>2</sup> – WP100/21
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	1000 V
<b>Maximum current (rated cross-section)</b>	57 A
<b>Caliber</b>	A6
<b>Electrical characteristics according to UL Standard</b>	
<b>Maximum voltage AC/DC</b>	600 V
<b>Maximum current (rated cross-section)</b>	57 A
<b>Section (min-max)</b>	20-6 (AWG)
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Maximum voltage AC/DC</b>	500 V
<b>Maximum current (rated cross-section)</b>	57 A
<b>Operating temperature Min/Max</b>	-40 °C / +80 °C
<b>Rated impulse withstand voltage / pollution degree</b>	8 kV / 3
<b>Insulation stripping length</b>	18 mm
<b>Width (pitch)</b>	10 mm
<b>Length</b>	71 mm
<b>Height mounted on TH35-7.5/TH35-15/G32</b>	53 / 61 / – mm
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
<b>Grey</b>	HMT.10/PT/GR (cod. HM331GR)
<b>Blue</b>	HMT.10/PT (Ex)i (cod. HI331)
<b>Thickness</b>	1.5 mm
<b>Cross-connection</b>	
<b>Model A)</b>	PTC/11/... (cod. PTC11...)
<b>Model B)</b>	–
<b>Rated current carrying capacity IEC/ATEX</b>	–
<b>Cross-connection identification strip</b>	–
<b>Coloured partition plate</b>	DFH/4/R (cod. DH04R)
<b>Cross-connection barrier</b>	–
<b>Test plug</b>	SDD/1 (cod. DD001)
<b>Modular test plug</b>	–
<b>End section for modular test plug</b>	–
<b>Marking</b>	
<b>Single marking tag</b>	CNU/8/51 (cod. NU0851S)
<b>Single marking tag for pitch insertion</b>	–
<b>End bracket</b>	
<b>TH35 screw type</b>	BT/3 (cod. BT003)
<b>TH35 snap-fit type</b>	BTO (cod. BT007)
<b>TH35 and G32 snap-fit type</b>	BTU (cod. BT005)
<b>DIN rail according to IEC 60715/TH35</b>	PR/3/..
<b>APPROVALS AND MARKINGS</b>	



1 For more details on accessories, refer to the relevant chapters

## DESCRIZIONE DEL PRODOTTO

HMM.10/GR Spring-clamp terminal block 10mm<sup>2</sup>, 1-level, grey color