

PRODUCT DATASHEET

LN INV DI 1200 P 54W 930 DAVR SN BK

LINEAR INDIVILED DIRECT/INDIRECT 1200 DALI SENSOR | Pendant luminaire for single or light line office application with CRI90 and DALI sensor, 1200 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct and indirect lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- Pendant luminaires with direct light emission (70%) and indirect light emission (30%)
- High performance with CRI90 and up to 137 lm/W
- IoT-ready luminaire with DALI-2 driver, suitable for VIVARES and other Light Management Systems
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Suitable for battery emergency installations acc. to EN 60598-2-22
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color



- Includes EVERLOOP: Convenient replacement of light source and LED driver
- PIR-Sensor with leader-follower function
- Combined daylight and motion detection
- Individual adjustment of the parameters with configuration software or remote control
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separately)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Lifetime (L80/B10): 70,000 h (at 25 °C)


TECHNICAL DATA

Electrical data


Nominal wattage	54 W / 48 W / 43 W / 34 W
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	233...205...195...160 mA
Inrush current	25.2 A
Inrush current time T_{h50}	40 μ s
Max. number of luminaires per miniature circuit breaker B16	29
Max. number of luminaires per miniature circuit breaker C10	23
Max. number of luminaires per miniature circuit breaker C16	22
Power factor λ	≥ 0.90
Total harmonic distortion	≤ 20 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / IoT

Photometrical data

Luminous flux	4250 lm / 5100 lm / 5650 lm / 6400 lm
Luminous efficacy	125 lm/W / 119 lm/W / 118 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 90
Standard deviation of color matching	< 3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	≤ 1
Stroboscope effect metric (SVM)	≤ 0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 ° + 130 °
UGR	< 19




LN INV DI 1200 P 54W 930 DAVR SN BK



LN INV DI 1200 P 54W 930 DAVR SN BK

Dimensions & Weight

Length	1210.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3590.00 g



LN INV 1200 P

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	DALI2
Mounting type	Suspended
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1400 mA
ECG - Output ripple current	≤ 3 %
Recommended control gear	OSRAM type OTI DALI 50/220-240/1A4 NFC L

Sensor

Type of sensor	Motion / Light
Sensor technology	Passive infrared/Photocell
Sensor detection angle	80 °
Sensor controlled switching time	10 s ... 30 min
Detection range of motion sensor	1.7 m ... 4 m


Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	By the end consumer





Additional product data




Added function	EVERLOOP / VIVARES / Programmable Multi Lumen
----------------	---

Accessories Mandatory

Product image	Product name	EAN
	LN INV SUSPENSION KIT BK	4099854297069

Accessories Optional







Product image	Product name	EAN
		4099854297083
	LN INV INFILL 600 BK	4099854297045
	LN INV INFILL 1200 BK	4099854297007
	LN INV INFILL 1500 BK	4099854297021



Product image	Product name	EAN
	LN INV SUSPENSION WIRE	4099854215551
	LN INV 1200 THROUGHWIRING KIT	4099854214820
	LN INV INLINE CONNECTOR	4099854215612






EQUIPMENT / ACCESSORIES



- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available


DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	LN INV P DAVR SN
 Legal information	Legal Insert LN INV P DA
 Legal information	LSI LN INV DA
 Declarations of conformity	LN INV
 Declarations of conformity UKCA	LN INV
 Certificates	LN INV

Photometric and lighting design files	Document name
 IES file (IES)	LN INV DI 1200 P 54W 930 DAVR SN BK
 LDT file (Eulumdat)	LN INV DI 1200 P 54W 930 DAVR SN BK

Photometric and lighting design files		Document name
	ULD file (DIALux)	LN INV DI 1200 P 54W 930 DAVR SN BK
	ROLF file (RELUX)	LN INV DI 1200 P 54W 930 DAVR SN BK
	UGR file (UGR table)	LN INV DI 1200 P 54W 930 DAVR SN BK
	Light distribution curve type cone	LN INV DI 1200 P 54W 930 DAVR SN BK
	Light distribution curve type polar	LN INV DI 1200 P 54W 930 DAVR SN BK

CAD/BIM files		Document name
	BIM Revit 3D	Linear Indiviled G2
	CAD STEP 3D	LN INV D I 1200 G2

Tender texts	Document name
	Tender documents LINEAR INDIVILED DIRECT INDIRECT 1200 DALI SENSOR P 54W 930 DAVR SN BK-EN



LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854371769	Folding box 1	178 mm x 1,263 mm x 103 mm	4190.00 g	23.16 dm ³
4099854371776	Shipping box 2	1,297 mm x 197 mm x 224 mm	9780.00 g	57.23 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

LINEAR DIMENSION DRAWING DALLI SN BK	DIMENSION	DIRECT	INDIRECT	TUMI	M ²	DALI	PAGE
LN INV DI 1200 P 54W 930 DAVR SN BK	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1
LN INV DI 1200 P 54W 930 DAVR SN BK	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1
LN INV DI 1200 P 54W 930 DAVR SN BK	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1
LN INV DI 1200 P 54W 930 DAVR SN BK	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1
	OSRAM	1200	47.24	1200	15.748	0.00	1



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.