


**Modular**  
screw terminal block 4mm<sup>2</sup>, 2-poles, flat connection, beige color

<b>Series</b>	BPL-TPL
<b>Code</b>	BP310
<b>Type</b>	BPL.4/PS/A
<b>HS code</b>	85369010
<b>Colour</b>	Beige
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Feed-through with solder terminal
<b>Rated cross-section</b>	4 mm <sup>2</sup>
<b>Rated cross-section</b>	-
<b>Connecting capacity</b>	
<b>Flexible wire</b>	0.5-4 mm <sup>2</sup>
<b>Rigid wire</b>	0.5-6 mm <sup>2</sup>
<b>Wire with ferrule - ferrule type</b>	4 mm <sup>2</sup> - WP40/16
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	500 V
<b>Maximum current (rated cross-section)</b>	32 A
<b>Caliber</b>	A4
<b>Electrical characteristics according to UL Standard</b>	
<b>Maximum voltage AC/DC</b>	300 V
<b>Maximum current (rated cross-section)</b>	20 A
<b>Section (min-max)</b>	18-12 (AWG)
<b>Tightening torque value (UL)</b>	4.4 lb.in
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Maximum voltage AC/DC</b>	-
<b>Maximum current (rated cross-section)</b>	-
<b>Rated impulse withstand voltage / pollution degree</b>	6 kV / 3
<b>Insulation stripping length</b>	9 mm
<b>Tightening torque value (nom. / max.)</b>	0.5 / 0.7 Nm
<b>Dimension</b>	20x24x36 mm (AxBxH)
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	-
<b>Insulated bushing</b>	-
<b>APPROVALS AND MARKINGS</b>	



## DESCRIZIONE DEL PRODOTTO

BPL.4/PS/A Modular screw terminal block 4mm<sup>2</sup>, 2-poles, flat connection, beige color