

PRODUCT-DETAILS

# PS1/38/6

## PS1/38/6 Busbar



### General Information

Extended Product Type	PS1/38/6
Product ID	2CDL210005R0638
EAN	4016779580816
Catalog Description	PS1/38/6 Busbar
Long Description	Busbar PS 1/38/6

### Technical

Standards	IEC/EN 60947-1
Suitable For	S200 F200 DDA200
Suitable for Product Class	wiring of auxiliary contacts
Rated Operational Voltage	690 V AC/DC Maximum 690 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	25 kA
Rated Uninterrupted Current ( $I_u$ )	40 A
Rated Frequency (f)	50 / 60 Hz DC
Pitch	44698.0

Number of Poles	38
Number of Phases	1
Number of Mountable Devices	38
	38
Overvoltage Category	III
Accessory Type	Busbar
Connection Type	Pin
Housing Material	Light grey, RAL 7035
Mounting Position	any
RAL Number	RAL 7035 - Light Grey
Color	grey
Rated Cross-Section	6 mm <sup>2</sup>

## Environmental

Pollution Degree	2
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK108468A1264
Environmental Information	DIN EN 60068
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Width in Number of Modular Spacings	57
Product Net Width	15 mm
Product Net Height	13 mm
Product Net Depth / Length	1012 mm
Product Net Weight	0.092 kg

## Ordering

Minimum Order Quantity	1 piece
Package Level 1 Units	50 piece
Package Level 1 Gross Weight	4.81 kg

## Certificates and Declarations

Declaration of Conformity - CE	9AKK108468A1264
--------------------------------	-----------------

## Installation

Instructions and Manuals	2CSC400002D0208
--------------------------	-----------------

## Popular Downloads

