

# NOCTIS LUX 3

SLI029049NW\_CZUJNIK\_PW



See  
more

Floodlight NOCTIS LUX 3, with a power of 20 W, high light efficacy 100 lm/W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP44

IK07



|                 |                       |                           |               |
|-----------------|-----------------------|---------------------------|---------------|
| Power           | <b>20 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux*  | <b>2000 lm (120°)</b> | Colour temperature        | <b>4000 K</b> |
| Colour of light | <b>Neutral white</b>  | Beam angle                | <b>100 °</b>  |
| IK              | <b>07</b>             | Degree of protection (IP) | <b>IP44</b>   |


## Technical data

|                              |                        |
|------------------------------|------------------------|
| Code                         | SLI029049NW_CZUJNIK_PW |
| Power                        | 20 W                   |
| Nominal current              | 90 mA                  |
| Voltage                      | 230 V                  |
| Energy consumption           | 20 kWh/1000h           |
| Frequency                    | 50HZ Hz                |
| Protection class             | I                      |
| Power supply included        | +                      |
| Power factor                 | 0.9                    |
| Useful luminous flux*        | 2000 lm (120°)         |
| Luminous flux**              | 2000 lm (360°)         |
| Lamp efficacy                | 100 lm/W               |
| Colour temperature           | 4000 K                 |
| Colour of light              | Neutral white          |
| Beam angle                   | 100 °                  |
| RA                           | >70                    |
| Uniformity of color SDCM max | 5                      |
| Dimmable                     | No                     |
| Working temperature range    | -20/+40 °              |
| Lifespan                     | 17000 h                |
| Housing material             | Aluminum, GLASS        |
| IK                           | 07                     |
| Degree of protection (IP)    | IP44                   |
| Colour                       | Black                  |
| Dimension (AxBxC)            | 120x170x53 mm          |
| For use                      | Outside                |
| Assembly method              | On the ceiling         |
| Application                  | EXT                    |
| Made in                      | PRC                    |



## Related documents



 Declaration of Conformity



 Photometric file

