

## PRODUCT DATASHEET DIM MCU G2

DIM MCU | Light management systems



---

### Areas of application

- Conference rooms
- Restaurants
- Shop lighting

---

### Product benefits

- Intuitive manual dimming and switching
- Individual setting of minimal brightness level

---

### Product features


- Switching load contact: 250 V/6 A (10 1-lamp or 5 2-lamp ECGs)
- Cover and rotary knob in cream white

## TECHNICAL DATA

### Electrical data

Nominal voltage	230 V
Mains frequency	50/60 Hz

### Dimensions & Weight



Length	71.00 mm
Mounting hole spacing, length	60,0 mm
Width	71.00 mm
Height	40.00 mm
Product weight	88.00 g

### Colors & materials

Product color	White
---------------	-------

### Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

### Capabilities

Dimmable	Yes
Dimming interface	1...10 V
Type of installation	Integrated in flush device box

### Certificates & Standards

Approval marks – approval	CE / EAC / UKCA
Protection class	II
Type of protection	IP20

Energy efficiency class

A1

## EQUIPMENT / ACCESSORIES

- Suitable for up to 50 electronic control gears (external load contact required)
- Flexible expansion via external load contact and via signal amplifier DIM SA
- Cover and rotary knob included

## DOWNLOAD DATA

### Documents and certificates



User instruction



Declarations Of Conformity CE



Declarations Of Conformity UKCA

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172224642	Folding box 1	85 mm x 85 mm x 65 mm	133.00 g	0.47 dm <sup>3</sup>
4062172224659	Shipping box 48	362 mm x 270 mm x 288 mm	6820.00 g	28.15 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.