# Product Data Sheet

## GW62548

#### IEC 309 BTS Range



A range of trailing and fixed plugs and socket-outlets for industrial use, complying with the dimensional and performance standards unified at International level (IEC 60309) and assimilated by the European Standards (EN 60309) and Italian Standards (CEI 23-12). Socket-outlets and plugs with a rated current of 63 and 125A are equipped with an extra pilot contact (CP) for creating an electric interlock. The range is completed with 90° fixed plugs and 10° and 90° fixed socket-outlets. Sleeves and pins are obtained from solid brass bar, type Pt. CuZn40Pb2 (Cu 58%, Zn 40%, Pb 2%); anti-loosening terminals with unlosable screws, and built-in cable clamp with anti-abrasion cable gland.

Colour	Violet	Rated current (A)	32
IP degree	IP44	No. of poles	3P
Mechanical resistance	IK08	Reference h	<u>-</u>
Туре	90° angled surface-mounting socket-outlet	Rated voltage	20-25 V
Frequency	50 - 60 Hz	Terminal tightening capacity	2.5-6mm² flexible cables - 2.5-10mm² rigid cables
Operating temperature	-25 +40 °C	Type of wiring	With screw
Electrocod	2210	Glow wire test	850 °C (active parts) - 650 °C (passive parts)
Total number of operations	> 2000	Permissible overload	42 A
Breaking capacity at 1.1 Un	40 A	Insulation resistance	> 10 MΩ
Thermo-pressure with ball	125 °C (active parts) - 80 °C (passive parts)		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS												
Saline solution	Acids		Bases		Solvents			Mineral	UV			
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Alcohol	oil	rays		
Resistant	Not resistant	L <mark>imite</mark> d resistance	L <mark>imite</mark> d resistance	Resistant	Resistant	Resistant	Resistant	Resistente	Resistant	Resistant		

#### **DIMENSIONAL**

### **TECHNICAL SYMBOLOGY**

IP

IK

With screw

GWT

•

850 °C (active parts) 125 °C (active parts) - 650 °C (passive parts) - 80 °C (passive parts)

### STANDARDS/APPROVALS

