



## **AKSR2/1**

Kala 600mm Surface and Recessed Kit (with driver)



Accessory for Kala

Technical Specifications:

Colour / Finish | [White]

Material | [Stainless Steel]

Dimmable | Yes

Dimmable Type | [Mains (Triac)]

IP Rating | IP20

Mounting Option | [Ceiling],[Recessed]

Class Protection | 1

Internal / External | Internal

OCTO Category | OCTO options available

Warranty (Years) | 5  
CE Mark | Yes  
UKCA Mark | Yes  
Length | 1,500  
Diameter | 180  
Height | 40  
Cut-Out Size | 200-220mm  
RAL Colour | 9,016  
Standard Product | Yes  
Wattage | 45W  
Lumens Delivered | 4800lm (4000K)  
Lumens Delivered Category | 3501-5000lm  
lm/W | 120lm/W  
lm/W Category | [>120lm/W]  
Beam Angle | 110  
Input | 220/240V  
Hertz | 50/60Hz  
Operating Temp | -10°C - 45°C  
SDCM | 6  
UGR | 28  
UGR Category | [UGR>19]  
Inrush Current | 31A 410us  
Running Current | 1050mA  
Lumen Depreciation | L80 50,000h  
Lumen Depreciation L70 B50 | L70 B50 60,000h  
Lumen Depreciation L80 | L80 54,000h  
Lumen Depreciation L90 | L90 51,000h

## Technical Data - ETIM - Electrical accessories for luminaires (EC002556)

---

Type of accessory	Other
-------------------	-------

---

Colour	White
--------	-------

---

Number of cores	0
-----------------	---

---

Datasheet generated from <https://onetimepim.com> last updated Friday, February 16, 2024 4:47:49 PM