


Screw
terminal block 95mm², blue color



| | |
|---|--|
| Series | GPA |
| Code | GA110 |
| Type | GPA.95 (Ex)i |
| HS code | 85369010 |
| Colour | Blue |
| TECHNICAL FEATURES | |
| Function/Type | Feed-through |
| Rated cross-section | 95 mm ² |
| Connecting capacity | |
| Flexible wire | 10-95 mm ² |
| Rigid wire | 10-120 mm ² |
| Wire with ferrule - ferrule type | - |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 1000 V |
| Maximum current (rated cross-section) | 232 A |
| Caliber | B12 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | 232 A |
| Section (min-max) | 2-250 MCM (AWG) |
| Tightening torque value (UL) | 90 lb.in |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | - |
| Maximum current (rated cross-section) | - |
| Operating temperature Min/Max | - |
| ensione impulsiva nom. / grado di inquinamento | 12 kV / 3 |
| Insulation stripping length | 30 mm |
| Tightening torque value (nom. / max.) | - |
| Width (pitch) | 26 mm |
| Length | 98 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 87 / 95 / 91 mm |
| Height for panel mounting | - |
| Length mounted on panel | - |
| Fixing distance between center | - |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| Cross-connection | |
| Model A) | - |
| Model B) | - |
| Rated current carrying capacity IEC/ATEX | - |
| Multiple cross-connection bar | - |
| Shunting screw and sleeve (Standard / Exe) | - |
| Protection cover | - |
| Coloured partition plate | - |
| Test plug socket | - |
| Marking | |
| Single marking tag | CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S) |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| Mounting rail | |
| IEC 60715/TH35 | PR/3/... |
| IEC 60715/G32 | PR/DIN/... |
| APPROVALS AND MARKINGS | |



* Panel mountable version with M6 screw* GPA.70 allow to create parallel connections

DESCRIZIONE DEL PRODOTTO

GPA.95(EX)I Screw terminal block 95mm², blue color