

# PRODUCT DATASHEET CONVERSION KIT + LED TUBE T5 AC HO80 P 1449 mm 36W 840

LED TUBE T5 CONVERSION KIT SINGLE LAMP | T5 LED tubes including conversion kit for single lamp luminaires



#### Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Offices, public buildings
- Supermarkets and department stores
- Industry

#### **Product benefits**

- Only around 5 minutes per luminaire needed for rewiring
- No ECG compatibility issues
- No ECG maintenance necessary
- No bending thanks to glass technology
- Shatter protection thanks to special PET coating
- High luminous flux for sophisticated lighting tasks

#### **Product features**

- Contains 10 LED TUBE T5 220-240V AC LED tubes and 10 conversion kits for single-lamp luminaires
- Conversion kit contains all necessary material for conversion of ECG luminaires to AC mains
- Detailed step-by-step instruction for guaranteed TÜV-certification available
- LED replacement for T5 fluorescent lamps with G5 base on AC mains
- Lamp tube made of glass with splinter protection e.g. for food industry applications



- High color consistency: ≤ 5 SDCM
- Lifetime: up to 50,000 h
- Low flicker according to EU 2019-2020 (SVM  $\leq$  0,4 / PstLM  $\leq$  1)
- Type of protection: IP20

# **TECHNICAL DATA**

#### **Electrical data**

Nominal wattage	36 W
Nominal voltage	220240 V
Nominal current	160 mA

# Photometrical data

Luminous flux	5600 lm
Luminous efficacy	155 lm/W
Light color	840

# Light technical data

Beam angle	190 °

# **Dimensions & Weight**

Product weight	2030.00 g

#### Additional product data

Product remark  TUBE T5 AC HO80 P 1449 mm 36W 840, EAN: 4058075824072, LED tube EEC: D	Product remark	11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
--	----------------	--

# Certificates & Standards

# Country-specific categorizations

Order reference	LEDTUBE T5AC HO

# Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- Not suitable for operation with electronic control gear.
- Not suitable for emergency lighting

#### **DOWNLOAD DATA**

# Documents and certificates Installation guide

# **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854108440	Shipping box 1	1,515 mm x 150 mm x 95 mm	2958.00 g	21.59 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# References / Links

- For current information see www.ledvance.com/ledtube

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.