

PRODUCT-DETAILS

S201MT-C25UC

S201MT-C25UC Miniature Circuit Breaker - 1P - C - 25 A



General Information

| | |
|-----------------------|--|
| Extended Product Type | S201MT-C25UC |
| Product ID | 2CDS271065R0254 |
| EAN | 4013614448386 |
| Catalog Description | S201MT-C25UC Miniature Circuit Breaker - 1P - C - 25 A |
| Long Description | S201MT-C25UC Miniature Circuit Breaker - 1P - C - 25 A |

Technical

| | |
|---|--|
| Standards | IEC/EN 60947-2 |
| Tripping Characteristic | C |
| Rated Operational Voltage | acc. to IEC 60898-1 220 V DC acc. to IEC 60898-1 253 V AC acc. to IEC 60947-2 253 V AC acc. to IEC 60947-2 220 V DC |
| Operational Voltage | Maximum (Incl. Tolerance) 250 V DC Maximum (Incl. Tolerance) 266 V AC Minimum 12 V AC Minimum 12 V DC |
| Rated Insulation Voltage (U _i) | acc. to IEC/EN 60664-1 484 V |
| Rated Impulse Withstand Voltage (U _{imp}) | 4 kV at 2000 μs at Sea Level 6.2 kV |
| Dielectric Test Voltage | 50/60 Hz, 1 min: 2 kV |
| Input Voltage Type | AC/DC |
| Rated Current (I _n) | 25 A |

| | |
|---|--|
| Rated Short-Circuit Capacity | (AC) 10 kA (220 V DC) 10 kA (230 V AC) 10 kA (253 V AC) 10 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (220 V DC) 10 kA (230 V AC) 10 kA (253 V AC) 10 kA |
| Rated Conditional Short-Circuit Current (I_{nc}) | (230 V) 10 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | (220 V DC) 10 kA |
| Rated Frequency (f) | 50 / 60 Hz DC |
| Power Loss | 2.62 W at Rated Operating Conditions per Pole 2.62 W |
| Power Supply Connection | Please Note Polarity of Device |
| Contact Position Indication | ON / OFF |
| Energy Limiting Class | 3 |
| Electrical Endurance | 1500 DC cycle 20000 AC cycle |
| Mechanical Endurance | 20000 cycle |
| Number of Poles | 1 |
| Number of Protected Poles | 1 |
| Overvoltage Category | III |
| Tightening Torque | 2.8 N·m |
| Actuator Type | Toggle |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Actuator Marking | I / O |
| Actuator Material | Insulation Group II, Black, Sealable |
| Housing Material | Insulation Group I, RAL 7035 |
| Options Provided | Suitable for traction application |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position | any |
| Recommended Screw Driver | Pozidriv 2 |
| Accessories Available | Yes |
| Remarks | Please note polarity of device |
| Connecting Capacity | Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ² |
| Installation Size | acc. to DIN 43880 1 |
| Terminal Type | Screw Terminals |

Environmental

| | |
|--|---|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +70 °C |
| Reference Ambient Air Temperature | 30 °C |
| Degree of Protection | IP20 IPXXB Enclosure with Cover IP40 |
| Pollution Degree | 3 |
| Environmental Conditions | 28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 % |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |

RoHS Status

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

| | |
|---|---|
| RoHS Information | 2CDK400602D2703 |
| REACH Declaration | 9AKK107492A1906 |
| SCIP | a62e1a07-4cd8-42e3-a6a1-8acf96626448 Germany (DE) |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Technical UL/CSA

| | |
|------------------------------------|------------------|
| Interrupting Rating acc. to UL1077 | (220 V DC) 10 kA |
|------------------------------------|------------------|

Dimensions

| | |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 1 |
| Product Net Width | 17.5 mm |
| Product Net Height | 88 mm |
| Product Net Depth / Length | 69 mm |
| Product Net Weight | 0.125 kg |
| Built-In Depth (t ₂) | 69 mm |

Ordering

| | |
|------------------------------|-----------------|
| Minimum Order Quantity | 1 piece |
| Package Level 1 Units | carton 10 piece |
| Package Level 1 Gross Weight | 1.3 kg |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Certification Agency | EN IEC |
| Declaration of Conformity - CE | 2CDK400602D2704 |

Installation

| | |
|--------------------------|-----------------|
| Instructions and Manuals | 2CDS207104P0002 |
|--------------------------|-----------------|

Popular Downloads

| | |
|-----------------------------------|--------------------|
| Data Sheet, Technical Information | No document needed |
|-----------------------------------|--------------------|

Classifications

| | |
|------------------------------------|--|
| ETIM 8 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 9 | EC000042 - Miniature circuit breaker (MCB) |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |
| CN8 | 8536 20 10 |
| UNSPSC | 39121603 |
| eClass | V11.0 : 27141901 |
| IDEA Granular Category Code (IGCC) | 4897 >> Miniature circuit breakers |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

