



MASTER PL-L 40W/830/4P 1CT/25

MASTER PL-L is a medium to high-wattage linear compact fluorescent lamp, typically used for general-illumination ceiling luminaires in retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. It is designed for operation on electromagnetic as well as electronic HF control gear and is provided with a plug-in/pull-out lamp base.

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- $\boldsymbol{\cdot}$ Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	2G11 [2G11]
Flux measurement reference	Sphere
Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	3,500 lumen
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.44
Chromaticity Coordinate Y (Nom)	0.403
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	88 lm/W

Color rendering index (CRI)	82
Operating and Electrical	
Power Consumption	40.0 W
Lamp Current (Nom)	0.320 A
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Mercury (Hg) Content (Max)	2 mg
Mercury (Hg) Content (Nom)	2.0 mg


Datasheet, 2023, May 15 data subject to change

MASTER PL-L 4 Pin

Energy Consumption kWh/1000 h	40 kWh
EPREL Registration Number	423,311
Product Data	
Full product code	871150061094240
Order product name	MASTER PL-L 40W/830/4P 1CT/25
Order code	927908208370

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	927908208370
Full product name	MASTER PL-L 40W/830/4P 1CT/25
EAN/UPC - Case	8711500610959


Dimensional drawing



 Product
 D (max)
 D1 (max)
 A (max)
 B (max)
 C (max)

 MASTER PL-L 40W/830/4P 1CT/25
 39.0 mm
 18.0 mm
 509.2 mm
 535 mm
 541.6 mm

Photometric data



Spectral Power Distribution Colour - MASTER PL-L 40W/830/4P 1CT/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.