

DURE 3

SLI043012WW_PW

See
more

Downlight luminaire DURE 3, with a power of 24 W, high light efficacy 121 lm/W. It has a high IP54 rating, making it ideal for use in rooms with high humidity. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

IP54

IK06



Power	24 W	Voltage	230 V
Luminous flux*	2900 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	110 °
IK	6	Degree of protection (IP)	IP54


Technical data

Code	SLI043012WW_PW
Power	24 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	2900 lm (360°)
Luminous flux**	1900 lm (360°)
Lamp efficacy	121 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC+PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	220x220x34 mm
Mounting hole	195x195 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



Related documents



 User manual



 Declaration of Conformity



 Photometric file

