DL200 Downlight Round 15W 1120lm 4000K 120° G2



PRODUCT INFORMATION

Product code 60365
Product code (long) IE-DL-DLR190-15-1120-4000KProduct description DL200 Downlight Round 15W
EAN code 5999097603650
Category Downlight

PHOTOMETRIC DATA

Nominal luminous flux 1120 lm Rated luminous flux 1200 lm Rated useful luminous flux 75 Nominal beam angle (half-peak value) 110° Rated beam angle (half-peak value) 110° Correlated colour temperature 4000K Colour temperature designation neutral white 80 Ra Colour rendering index (Ra) 6 SDCM Colour consistency Warm-up time to reach 60% of full light 2 s Suitable for accent lighting

ELECTRICAL DATA

Nominal wattage 15W
Rated wattage 15W
Nominal voltage 220-240V
Operating frequency 50/60Hz
Nominal current 300 mA
Power factor 0.9

Overal diameter 200 mm
Overall width 21 mm
Lamp shape Round
Weight 0,600 kg
Mounting Recessed

LIFE SPAN

Nominal life time 30 000 hrs
Rated life time 30 000 hrs
Number of switching cycles 15000
Lumen main.fact.at end of nom.life time 0,7
Warranty 3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 3,0 s

Optimum operating ambient temperature -20°C - +40°C

Lamp finish Milky cover

Dimming non-dimmable

Energy efficiency class A+

Energy consumption 15 kWh/100h

Electrical protection class Class II

IP rating IP20



