

PRODUCT DATASHEET QTz8 4X18

QUICKTRONIC® QTz8 | ECG for T8/26 mm linear fluorescent lamps



Areas of application

- Public buildings
- Sports halls
- Strip lighting
- Suitable for luminaires of protection class I

Product benefits

- Compact housing
- Automatic restart after lamp replacement

Product features

Supply voltage: 220...240 V
Line voltage: 198...264 V
Line frequency: 50 Hz | 60 Hz
Energy Efficiency Index EEI: A2

- Number of lamp switching cycles: up to 3,500

TECHNICAL DATA

Electrical data

Nominal wattage	72.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Operating frequency	3045 kHz

Dimensions & Weight

Length	210.00 mm
Mounting hole spacing, length	200,0 mm
Width	40.00 mm
Height	30.00 mm
Product weight	155.00 g

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-15+50 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECC lifetime	70000 t 1)
ECG lifetime	30000 h ¹⁾

¹⁾ At maximum $\rm T_{\rm c}$ / 10% failure rate

Capabilities

Dimmable	No	
Max. cable length to lamp/LED module	2.0 m / 1.0 m	
Suitable for fixtures with prot. class	1	

Certificates & Standards

Approval marks – approval	CE / CQC

Protection class	П
Type of protection	IP20
Energy efficiency class	A3
EEI – Energy Label	A2

LOGISTICAL DATA

	Temperature range at storage	-40+85 °C
--	------------------------------	-----------

DOWNLOAD DATA

	Documents and certificates
PDF	User instruction
PDF	Declarations Of Conformity CE
PDF	Certificates

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321863362	Unpacked 1		150.00 g	
4008321863379	Shipping box 20	226 mm x 195 mm x 174 mm	3065.00 g	7.67 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.