

PRODUCT-DETAILS

# MLBL-09R

## MLBL-09R LED block



### Algemene informatie

Type	MLBL-09R
Artikelnummer	1SFA611621R1091
EAN	7320500544969
Omschrijving	MLBL-09R LED block

Omschrijving

The MLBL-09R LED block is: - Red - Illuminated - Front mounting - 415 V  
 This LED block is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.

### Ordering

Minimale bestelhoeveelheid	10 stuk
Numerus douanetarief	85369001

### Popular Downloads

Gegevensblad, technische informatie	1SFC151007C02__
Instructies en	1SFC151011M0201

handleidingen

---

## Dimensions

Product netto breedte	0.01 m
Product netto hoogte	0.044 m
Product netto diepte	0.042 m
Product netto gewicht	0.01 kg

---

## Technical

Omgevingsluchttemperatuur	Werking -25 ... +70 °C Opslag -40 ... +85 °C
Kleur	Red
Verlichting	Illuminated
Lichtbron	415 V AC, integrated LED
Montagetype	Front mounting
Beschermingsgraad	Terminals IP20
Toegekende frequentie (f)	50 / 60 Hz
Nominaal bedrijfsvoltage	415 V AC
Verbindingscapaciteit	Flexible with Ferrule 1 x 0.75...2.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.75...2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.75...2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.75...2.5 mm <sup>2</sup> Flexible 1 x 0.75 ... 2.5 mm <sup>2</sup> Flexible 2 x 0.75 ... 2.5 mm <sup>2</sup> Solid 1 x 0.75...2.5 mm <sup>2</sup> Solid 2 x 0.75...2.5 mm <sup>2</sup>
Aansluitwijze	Schroefklem
Terminaltype	Schroef
Aanhaalmoment	0.9 N·m
Kabelstriplengte	8 mm
Geschikt voor	MCBH-00 MCBH5-00 MP1 MP2 MP3 MP4 MPMT3 MPMP3 M2SS1 M2SS2 M2SS3 M2SS4 M2SS5 M2SS6 M3SS1 M3SS2 M3SS3 M3SS4 M3SS5 M3SS6 M3SS7 M3SS8 MPM1
Geschikt voor productklasse	Pilot Devices

---

## Technical UL/CSA

Verbindingscapaciteit	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

## Environmental

RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS-datum	0635 4
RoHS-informatie	2CMT2015-005452
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Business

## Certificates and Declarations

CB-certificaat	SEMKO_SE-56219
CQC-certificaat	CQC2008010305274953
cULus-certificaat	9AKK107046A9925
Declaration of Conformity - CCC	2020980305001106
Conformiteitsverklaring - CE	2CMT2015-005452
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL-certificaat	E-14107
EAC-certificaat	1SFC150017D1101

## Container Information

Pakketniveau 1 Units	tas 10 stuk
Pakketniveau 1 Breedte	0.135 m
Pakketniveau 1 Lengte	0.155 m
Pakketniveau 1 Hoogte	0.025 m
Pakketniveau 1 Bruto gewicht	0.11 kg
Pakketniveau 1 EAN	7320500372920

## Classifications

Object classificatiecode	E
ETIM 6	EC000204 - Signaalamphouder
ETIM 7	EC000204 - Lamp holder block for control circuit devices
ETIM 8	EC000204 - Signaalamphouder
eClass	V11.0 : 27371209
UNSPSC	39122221
IGCC (IDEA granulaire categoriecode)	5219 >> Switch part or accessory
E-Number (Finland)	2315785
E-Number (Sweden)	3705633

---

## Categorieën

---

Laagspanningsproducten en -systemen → Control Producten → Drukknoppen → Drukknoppen

Laagspanningsproducten en -systemen → Control Producten → Drukknoppen → Drukknoppen toebehoren

