## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| _    | •  |       |        |     |
|------|----|-------|--------|-----|
| Tyna | Λt | light | source | ٠.  |
| IVDE | vı | HEILL | JUUILE | - • |

| Product parameters            |        |                                 |      |  |  |
|-------------------------------|--------|---------------------------------|------|--|--|
| Anti-glare shield:            | No     | Dimmable:                       | Yes  |  |  |
| High luminance light source:  | No     |                                 |      |  |  |
| Colour-tuneable light source: | No     | Envelope:                       | -    |  |  |
| Mains or non-mains:           | NMLS   | Connected light source (CLS):   | No   |  |  |
| (or other electric interface) |        |                                 |      |  |  |
| Light source cap-type         | G24Q-3 |                                 |      |  |  |
| Lighting technology used:     | CFLni  | Non-directional or directional: | NDLS |  |  |
|                               | 1      |                                 |      |  |  |

## **Product parameters**

|   |  | 1 Todact parai            |  |              |  |  |
|---|--|---------------------------|--|--------------|--|--|
| Parameter   |  | Value                     | Parameter  | Value        |  |  |
| General product parameters:   |  |                           |  |              |  |  |
| <u> </u>  | mption in on-<br>100 h), rounded<br>est integer                              | 28                        | Energy efficiency class  | G            |  |  |
| indicating if it r in a sphere (3   | us flux (фuse),<br>refers to the flux<br>60º), in a wide<br>in a narrow cone | 1 800 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |  |  |
| On-mode pexpressed in W   | oower (P <sub>on</sub> ),  | 27,4                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal |  | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |  |  |
| Outer dimensions without  | Height   | 163                       | Spectral power   | See image    |  |  |
|   | Width  | 27                        | distribution in the  | in last page |  |  |
|   | Depth  | 27                        |  |              |  |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load |                |
|--|--------------------------------------|----------------|
| Claim of equivalent power <sup>(a)</sup>   | - If yes, equivalent power (W)       | -              |
|  | Chromaticity coordinates (x and y)   | 0,380<br>0,380 |

(a)'-': not applicable; (b)'-': not applicable;

