

PRODUCT-DETAILS

MLBL-05BG

MLBL-05BG LED block



Algemene informatie

Type	MLBL-05BG
Artikelnummer	1SFA611621R2052
EAN	7320500545324
Omschrijving	MLBL-05BG LED block

Omschrijving

The MLBL-05BG LED block is: - Green - Illuminated - Rear mounting - 110 ... 130 V DC
 This LED block is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.

Ordering

Minimale bestelhoeveelheid	10 stuk
Nummer douanetarief	85369001

Popular Downloads

Gegevensblad, technische informatie	1SFC151007C02_
Instructies en handleidingen	1SFC151011M0201

Dimensions

Product netto breedte	0.01 m
Product netto hoogte	0.044 m
Product netto diepte	0.042 m
Product netto gewicht	0.01 kg

Technical

Omgevingsluchttemperatuur	Werking -25 ... +70 °C Opslag -40 ... +85 °C
Kleur	Green
Verlichting	Illuminated
Lichtbron	110-130 V DC, integrated LED
Montagetype	Rear mounting
Beschermingsgraad	Terminals IP20
Nominaal bedrijfsvoltage	110 ... 130 V DC
Verbindingscapaciteit	Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ²
Aansluitwijze	Schroefklem
Terminaltype	Schroef
Aanhaalmoment	0.9 N·m
Kabelstriplengte	8 mm
Geschikt voor	MCBH-00 MCBH5-00 MP1 MP2 MP3 MP4 MPMT3 MPMP3 M2SS1 M2SS2 M2SS3 M2SS4 M2SS5 M2SS6 M3SS1 M3SS2 M3SS3 M3SS4 M3SS5 M3SS6 M3SS7 M3SS8 MPM1
Geschikt voor productklasse	Pilot Devices

Technical UL/CSA

Verbindingscapaciteit	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

Environmental

RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS-datum	0635 4
RoHS-informatie	2CMT2015-005452
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Business

Certificates and Declarations

CB-certificaat	SEMKO SE-56219
CQC-certificaat	CQC2008010305274953
cULus-certificaat	9AKK107046A9925
Declaration of Conformity - CCC	2020980305001106
Conformiteitsverklaring - CE	2CMT2015-005452
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL-certificaat	E-14107
EAC-certificaat	1SFC150017D1101

Container Information

Pakketniveau 1 Units	tas 10 stuk
Pakketniveau 1 Breedte	0.135 m
Pakketniveau 1 Lengte	0.155 m
Pakketniveau 1 Hoogte	0.025 m
Pakketniveau 1 Brutogewicht	0.11 kg
Pakketniveau 1 EAN	7320500373644

Classifications

Object classificatiecode	E
ETIM 6	EC000204 - Signaallamphouder
ETIM 7	EC000204 - Lamp holder block for control circuit devices
ETIM 8	EC000204 - Signaallamphouder
eClass	V11.0 : 27371209
UNSPSC	39122221
IGCC (IDEA granulaire categoriekecode)	5219 >> Switch part or accessory
E-Number (Finland)	2315816
E-Number (Sweden)	3705669

Categorieën

Laagspanningsproducten en -systemen → Control Producten → Drukknoppen → Drukknoppen
 Laagspanningsproducten en -systemen → Control Producten → Drukknoppen → Drukknoppen toebehoren
 Middenspanningsproducten → Service → Spares and Consumables → Parts → All Spare Parts (Relays-SWG-CB)

