


## SR D50 5000 FSP1000 IA HVIP GFK AL (105 565)



Figure without obligation



Supporting tube with interior sealing end and EB spring element. Air-termination tip  $\varnothing 10$  mm.

Type	SR D50 5000 FSP1000 IA HVIP GFK AL
Part No.	105 565
Material of air-termination tip	Al
Length of air-termination tip	1000 mm
Material of supporting tube	GRP / Al
Length of supporting tube	5000 mm
Outside diameter $\varnothing$	50 mm
Transport length	5000 mm
Wall thickness	4 mm
Material factor km	0.7
Length of insulating clearance	1800 mm
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Suitable for installation outside the tube	yes
Max. free length with air-termination tip (wall mounting)	4000 mm
Max. gust wind speed (wall mounting, 1x HVI power inside)	203 km/h
Max. gust wind speed (wall mounting, 1x HVI power inside + 1x HVI power outside)	181 km/h
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	7,92 kg
Customs tariff number	85389099
GTIN	4013364271944
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.