## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 9290023891

## Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type         | G4   |                                 |      |  |  |  |
| (or other electric interface) |      |                                 |      |  |  |  |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No   |  |  |  |
| Colour-tuneable light source: | No   | Envelope:                       | -    |  |  |  |
| High luminance light source:  | No   |                                 |      |  |  |  |
| Anti-glare shield:            | No   | Dimmable:                       | No   |  |  |  |
| Product parameters            |      |                                 |      |  |  |  |

|   |                                 | Product para            | neters  |              |  |  |
|---|---------------------------------|-------------------------|---|--------------|--|--|
| Parameter   |                                 | Value                   | Parameter   | Value        |  |  |
| General product parameters:   |                                 |                         |   |              |  |  |
| Energy consum<br>mode (kWh/100<br>up to the nearest   | 0 h), rounded                   | 2                       | Energy efficiency<br>class  | E            |  |  |
| Useful luminous<br>indicating if it re<br>in a sphere (36<br>cone (120 <sup>o</sup> ) or in<br>(90 <sup>o</sup> ) | fers to the flux 0°), in a wide | 215 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 3 000        |  |  |
| On-mode po<br>expressed in W  | ower (P <sub>on</sub> ),        | 1,8                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| Networked stand<br>for CLS, express<br>rounded to the s   | sed in W and                    | -                       | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |
| Outer   | Height                          | 35                      | Spectral power  | See image    |  |  |
| dimensions  | Width                           | 13                      | distribution in the   | in last page |  |  |
| without   | Depth                           | 13                      |   |              |  |  |
| I   |                                 | 1                       | 1   | Page 1       |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |      | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|--|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | Yes  | lf yes, equivalent power (W)            | 20    |  |  |  |
|  |      | Chromaticity                            | 0,434 |  |  |  |
|  |      | coordinates (x and y)                   | 0,403 |  |  |  |
| Parameters for LED and OLED light sources:   |      |   |       |  |  |  |
| R9 colour rendering index value 0  |      | Survival factor                         | 0,90  |  |  |  |
| the lumen maintenance factor   | 0,93 |   |       |  |  |  |
| (a)  | 1    |   |       |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

