

# SLI028024NW\_PW\_CASAMBI

SLI028024NW\_PW\_CASAMBI



Power	<b>20 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3250 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>10</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

Code	SLI028024NW_PW_CASAMBI
Power	20 W
Nominal current	150 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.92
Useful luminous flux*	3250 lm (360°)
Luminous flux**	3000 lm (360°)
Lamp efficacy	163 lm/W
Luminous intensity	1000 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	CASAMBI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Degree of protection (IP)	IP65
Colour	Gray/White
Dimension (AxBxC)	600x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,



