

PRODUCT DATASHEET LINEAR HOUSING 440 1XTUBE UVC SENSOR WT

UVC LINEAR HOUSING | Metal housing with PIR sensor for germicidal lamps



Areas of application

- Pharmacies
- Reception areas
- Hotels
- Production and assembly facilities
- Offices

Product benefits

- Highly effective purification and sterilization
- Safety ensured thanks to automatic switch off when people are detected in UV workspace
- 3 years guarantee

Product features

- Housing dedicated to T8 UVC G13
- Built-in IR sensor, safety kit with 30 seconds start delay
- Available in two lengths
- Anti-UV coating
- Easy operation and installation
- Equipped with a sensor fixed to the product



TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Total harmonic distortion	< 15 %
Protection class	1
Operating mode	Electronic control gear (ECG)

Dimensions & Weight

Length	604.00 mm
Width	54.00 mm
Height	75.00 mm
Product weight	615.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Steel ¹⁾
Glow Wire Test according to IEC 60695-2-12	650 °C

¹⁾ Sensor made of PC/PE (anti-UVC)

Application & Mounting

Type of connection	Terminal
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
Application environment	Indoor
With light source	No
Holder designation	G13

Sensor

Sensor technology	Passive infrared (PIR)	
Sensor detection angle	360 °	
Sensor controlled switching time	30 s	

Additional product data

Number of illuminants 1

DOWNLOAD DATA

Documents and certificates



Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075522084	Folding box 1	624 mm x 55 mm x 45 mm	676.00 g	1.54 dm ³
4058075522091	Shipping box 8	677 mm x 287 mm x 130 mm	6333.00 g	25.26 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.